



Message Implementation Guideline

Customer Orders XML

Model: Customer Order Axia GS1 BMS 3.1
Version: GS1 BMS 3.1
Variant: 16
Issue date: 2017-01-31
Author: Eva H Walldow

1 Structure	3
2 Guideline	6

Change Log CustomerOrder Axia

Date	Variant	Comments
2015-08-06	10	<code>Order/OrderLogisticalInformation/ShipTo/AdditionalPartyIdentificationTypeCode</code> Included
2015-08-06	10	<code>Order/OrderLogisticalInformation/InventoryLocation/gln</code> Included
2015-08-20	11	Date format changed to standard format CCYY-MM-DD for all elements below <code>Order/OrderLogisticalInformation/OrderLogisticalDateInformation</code>
2015-08-20	11	Time format changed to standard format HH:MM:SS for all elements below <code>Order/OrderLogisticalInformation/OrderLogisticalDateInformation</code>
2015-09-22	12	<code>Order/OrderLineItem/additionalOrderLineInstruction</code> included for text to be written on the delivery note
2015-10-12	13	Code 'C' for Cutting added in <code>Order/OrderInstruction code</code>
2015-11-10	14	<code>/Order:OrderMessage/Order/OrderLogisticalInformation/shipTo/contact/communicationChannel</code> for 'TE' and 'EM' included
2015-11-10	14	<code>/Order:OrderMessage/Order/OrderLogisticalInformation/shipTo/contact/communicationChannel/communicationValue</code> for mail address and Phone number included
2016-05-30	15	<code>/Order:OrderMessage/Order/transactionalTradeItem/additionalTransactionalTradeItemIdentification</code> included for Customer Order number <code>Order:OrderMessage/Order/transactionalTradeItem/transactionalTradeItemIdentification/additionalTransactionalTradeItemIdentificationTypeCode = 'ON'</code>
2017-01-31	16	<code>/Order:OrderMessage/Order/transactionalTradeItem/additionalTransactionalTradeItemIdentification</code> included for Customer Order number <code>Order:OrderMessage/Order/transactionalTradeItem/transactionalTradeItemIdentification/additionalTransactionalTradeItemIdentificationTypeCode = 'ZFX'</code>
2017-01-31	16	<code>Order/OrderLineItem/monetaryAmountExcludingTaxes</code> added for Custom value



Structure

Occurrence	Element/Attribute
	orderMessage
1 .. 1	xsd:sequence
1 .. 1	sh:StandardBusinessDocumentHeader
1 .. 1	xs:sequence
1 .. 1	HeaderVersion
1 .. unbounded	Sender
1 .. 1	xs:sequence
1 .. 1	Identifier
	<i>Authority</i>
1 .. unbounded	Receiver
1 .. 1	xs:sequence
1 .. 1	Identifier
1 .. 1	DocumentIdentification
1 .. 1	xs:sequence
1 .. 1	Standard
1 .. 1	TypeVersion
1 .. 1	InstanceIdentifier
1 .. 1	Type
1 .. 1	CreationDateAndTime
1 .. 10000	order
1 .. 1	xs:sequence
1 .. 1	creationDateTime
1 .. 1	documentStatusCode
1 .. 1	xs:sequence
1 .. 1	orderIdentification
1 .. 1	xs:sequence
1 .. 1	entityIdentification
0 .. 1	orderTypeCode
1 .. unbounded	orderInstructionCode
0 .. 1	additionalOrderInstruction
required	<i>languageCode</i>
0 .. 1	note
required	<i>languageCode</i>
1 .. 1	buyer
1 .. 1	xs:sequence
0 .. 1	gln
0 .. unbounded	additionalPartyIdentification
required	<i>additionalPartyIdentificationTypeCode</i>
1 .. 1	seller
1 .. 1	xs:sequence
0 .. 1	gln
0 .. unbounded	additionalPartyIdentification
required	<i>additionalPartyIdentificationTypeCode</i>
1 .. 1	orderLogisticalInformation
1 .. 1	xs:sequence
0 .. 1	shipTo
1 .. 1	xs:sequence
0 .. 1	gln
0 .. unbounded	additionalPartyIdentification

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
required	<i>additionalPartyIdentificationTypeCode</i>
0 .. 1	address
1 .. 1	xsd:sequence
0 .. 1	city
0 .. 1	countryCode
0 .. 1	name
0 .. 1	postalCode
0 .. 1	streetAddressOne
0 .. 1	streetAddressTwo
0 .. unbounded	contact
1 .. 1	xsd:sequence
0 .. unbounded	communicationChannel
1 .. 1	xsd:sequence
1 .. 1	communicationChannelCode
1 .. 1	communicationValue
0 .. 1	inventoryLocation
1 .. 1	xsd:sequence
0 .. 1	gln
0 .. unbounded	additionalPartyIdentification
required	<i>additionalPartyIdentificationTypeCode</i>
0 .. 1	orderLogisticalDateInformation
1 .. 1	xsd:sequence
0 .. 1	requestedDeliveryDateRange
1 .. 1	xsd:sequence
0 .. 1	beginDate
0 .. 1	beginTime
0 .. 1	endDate
0 .. 1	endTime
0 .. 1	requestedDeliveryDateTime
1 .. 1	xsd:sequence
1 .. 1	date
0 .. 1	time
0 .. 1	shipmentTransportationInformation
1 .. 1	xsd:sequence
0 .. unbounded	handlingInstructionCode
0 .. 1	transportServiceCategoryType
0 .. 1	transportServiceLevelCode
0 .. 1	carrier
1 .. 1	xsd:sequence
0 .. unbounded	additionalPartyIdentification
required	<i>additionalPartyIdentificationTypeCode</i>
0 .. 1	deliveryTerms
1 .. 1	xsd:sequence
0 .. 1	deliveryInstructions
required	<i>languageCode</i>
1 .. unbounded	orderLineItem
1 .. 1	xsd:sequence
1 .. 1	lineItemNumber
1 .. 1	requestedQuantity
	<i>measurementUnitCode</i>
0 .. 1	additionalOrderLineInstruction

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
required	<i>languageCode</i>
0 .. 1	netPrice
required	<i>currencyCode</i>
0 .. 1	monetaryAmountExcludingTaxes
required	<i>currencyCode</i>
0 .. 1	note
required	<i>languageCode</i>
1 .. 1	transactionalTradeltem
1 .. 1	xsd:sequence
1 .. 1	gtin
0 .. unbounded	additionalTradeltemIdentification
required	<i>additionalTradeltemIdentificationTypeCode</i>
1 .. 1	xsd:sequence
0 .. 1	tradeltemDescription
required	<i>languageCode</i>

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Guideline

Element/Attribute	Annotation
orderMessage	Type order:OrderMessageType
xsd:sequence	Occurrence 1 .. 1
sh:StandardBusinessDocumentHeader	Occurrence 1 .. 1 Type sh:StandardBusinessDocumentHeader
xsd:sequence	Occurrence 1 .. 1
HeaderVersion	Occurrence 1 .. 1 Type xsd:string Example 3.1
Sender	Occurrence 1 .. unbounded Type sh:Partner
xsd:sequence	Occurrence 1 .. 1
Identifier	Occurrence 1 .. 1 Type sh:PartnerIdentification Remark Client Id - to be agreed Example 567819
<i>Authority</i>	Type xsd:string Example ZZ
Receiver	Occurrence 1 .. unbounded Type sh:Partner
xsd:sequence	Occurrence 1 .. 1
Identifier	Occurrence 1 .. 1 Type sh:PartnerIdentification Remark GLN (GS1 location code) for receiver of the message - to be agreed Example 7393321400011
DocumentIdentification	Occurrence 1 .. 1 Type sh:DocumentIdentification
xsd:sequence	Occurrence 1 .. 1
Standard	Occurrence 1 .. 1 Type xsd:string Example GS1 BMS
TypeVersion	Occurrence 1 .. 1 Type xsd:string Example 3.1
InstanceIdentifier	Occurrence 1 .. 1 Type xsd:string Example GS1
Type	Occurrence 1 .. 1 Type xsd:string Example Orders
CreationDateAndTime	Occurrence 1 .. 1 Type xsd:dateTime Remark message date/time Example 2015-02-02T12:10:00
order	Occurrence 1 .. 10000 Type order:OrderType
xsd:sequence	Occurrence 1 .. 1
creationDateTime	Occurrence 1 .. 1 Type xsd:dateTime Remark Document date/time Example 2015-02-02T12:10:00

Bold = Element, *Italic* = Attribute, Grey = Group



Element/Attribute	Annotation
documentStatusCode	Occurrence 1 .. 1 Type shared_common:DocumentStatusEnumerationType Remark Function Applicable Codes ORIGINAL
xsd:sequence	Occurrence 1 .. 1
orderIdentification	Occurrence 1 .. 1 Type shared_common:EntityIdentificationType Occurrence 1 .. 1
xsd:sequence	Occurrence 1 .. 1
entityIdentification	Occurrence 1 .. 1 Type restriction (xsd:string) Length 1 .. 35 Remark Ordernumber Example 125987
orderTypeCode	Occurrence 0 .. 1 Type ecom_common:OrderTypeCodeType Length 1 .. 80 Description 224 (Rush Order) only used by Bring Warehousing Example 220 Applicable Codes 220 Order 224 Rush order
orderInstructionCode	Occurrence 1 .. unbounded Type ecom_common:OrderInstructionCodeType Length 1 .. 80 Remark To be used for different services at Warehouse Example S Applicable Codes C Cutting N Normal S Sampakk
additionalOrderInstruction	Occurrence 0 .. 1 Type shared_common:Description1000Type Length 1 .. 1000 Remark Additional information to the Warehouse - as Shipping Conditions Example 02
languageCode	Type restriction (xsd:string) Length 1 .. 80 Use required Example NO Applicable Codes NO NORWAY
note	Occurrence 0 .. 1 Type shared_common:Description500Type Length 1 .. 500 Remark Consignor's or additional reference number Example 69581A
languageCode	Type restriction (xsd:string) Length 1 .. 80 Use required Example NO Applicable Codes NO
buyer	Occurrence 1 .. 1 Type ecom_common:TransactionalPartyType

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
<i>xsd:sequence</i>	Occurrence 1 .. 1
gln	Occurrence 0 .. 1 Type shared_common:GLNType Pattern \d{13} Remark GLN (GS1 location code) for buyer Example 7356099100013
additionalPartyIdentification	Occurrence 0 .. unbounded Type shared_common:AdditionalPartyIdentificationType Length 1 .. 80 Remark Customer id assigned by Bring and additionalPartyIdentificationTypeCode = '88' Example 50214
<i>additionalPartyIdentificationTypeCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example 88 Applicable Codes 87 Assigned by carrier 88 Assigned by the owner of operation
seller	Occurrence 1 .. 1 Type ecom_common:TransactionalPartyType
<i>xsd:sequence</i>	Occurrence 1 .. 1
gln	Occurrence 0 .. 1 Type shared_common:GLNType Pattern \d{13} Remark GLN for supplier Example 7356099100013
additionalPartyIdentification	Occurrence 0 .. unbounded Type shared_common:AdditionalPartyIdentificationType Length 1 .. 80 Remark Customer id assigned by Bring and additionalPartyIdentificationTypeCode = '88' Example 456783
<i>additionalPartyIdentificationTypeCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example 88 Applicable Codes 88 Assigned by the owner of operation
orderLogisticalInformation	Occurrence 1 .. 1 Type ecom_common:OrderLogisticalInformationType
<i>xsd:sequence</i>	Occurrence 1 .. 1
shipTo	Occurrence 0 .. 1 Type ecom_common:TransactionalPartyType
<i>xsd:sequence</i>	Occurrence 1 .. 1
gln	Occurrence 0 .. 1 Type shared_common:GLNType Pattern \d{13} Remark GLN for delivery party Example 7310500001005
additionalPartyIdentification	Occurrence 0 .. unbounded Type shared_common:AdditionalPartyIdentificationType Length 1 .. 80 Remark Customer id for delivery party Example 50296

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
<i>additionalPartyIdentificationTypeCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example 88 Applicable Codes 87 Assigned by carrier 88 Assigned by the owner of operation
address	Occurrence 0 .. 1 Type shared_common:AddressType
<i>xsd:sequence</i>	Occurrence 1 .. 1
<i>city</i>	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 200 Remark Ship to party city name Example Höganäs
<i>countryCode</i>	Occurrence 0 .. 1 Type shared_common:CountryCodeType Length 1 .. 80 Remark ISO 3166 alpha Example SE
<i>name</i>	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 200 Remark Ship to party name Example ICA Kvantum
<i>postalCode</i>	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 80 Remark Ship to postal code Example 26005
<i>streetAddressOne</i>	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 200 Remark Ship to, Street adress Example Köpmansgatan 10
<i>streetAddressTwo</i>	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 200 Example Adress rad 2
contact	Occurrence 0 .. unbounded Type shared_common:ContactType
<i>xsd:sequence</i>	Occurrence 1 .. 1
communicationChannel	Occurrence 0 .. unbounded Type shared_common:CommunicationChannelType
<i>xsd:sequence</i>	Occurrence 1 .. 1
communicationChannelCode	Occurrence 1 .. 1 Type shared_common:CommunicationChannelCodeType Length 1 .. 80 Example EM Applicable Codes EM Electronic mail TE Telephone
communicationValue	Occurrence 1 .. 1 Type restriction (xsd:string) Length 1 .. 200 Remark E-mail address / Telephone number

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
inventoryLocation	Example test.testsson@test.te Occurrence 0 .. 1 Type ecom_common:TransactionalPartyType
xsd:sequence	Occurrence 1 .. 1
gln	Occurrence 0 .. 1 Type shared_common:GLNType Pattern \d{13} Remark GLN for Warehouse location Example 7393321401018
additionalPartyIdentification	Occurrence 0 .. unbounded Type shared_common:AdditionalPartyIdentificationType Length 1 .. 80 Remark Warehouse location assigned by the owner of the operation Example BERGER
additionalPartyIdentificationTypeCode	Type restriction (xsd:string) Length 1 .. 80 Use required Example 88 Applicable Codes 4033 5500 BERGER BS07 BS17 BS19 BS24 NCD
orderLogisticalDateInformation	Occurrence 0 .. 1 Type ecom_common:OrderLogisticalDateInformationType
xsd:sequence	Occurrence 1 .. 1
requestedDeliveryDateRange	Occurrence 0 .. 1 Type shared_common:DateTimeRangeType
xsd:sequence	Occurrence 1 .. 1
beginDate	Occurrence 0 .. 1 Type xsd:date Remark Requested delivery date start (CCYY-MM-DD) Example 2015-06-20
beginTime	Occurrence 0 .. 1 Type xsd:time Remark Requested delivery time start (HH:MM:SS) Example 12:00:00
endDate	Occurrence 0 .. 1 Type xsd:date Remark Requested delivery date end (CCYY-MM-DD) Example 2015-06-20
endTime	Occurrence 0 .. 1 Type xsd:time Remark Requested delivery time start (HH:MM:SS) Example 16:00:00
requestedDeliveryDateTime	Occurrence 0 .. 1 Type shared_common:DateOptionalTimeType Remark Delivery date at customers site
xsd:sequence	Occurrence 1 .. 1

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation																						
<ul style="list-style-type: none"> date 	<p>Occurrence 1 .. 1 Type xsd:date Remark Delivery date at customers site (YYYY-MM-DD) Example 2014-10-01</p>																						
<ul style="list-style-type: none"> time 	<p>Occurrence 0 .. 1 Type xsd:time Remark Delivery time customers siteTime (HH:MM:SS) Example 14:00:00</p>																						
shipmentTransportationInformation	<p>Occurrence 0 .. 1 Type ecom_common:ShipmentTransportationInformationType</p>																						
<ul style="list-style-type: none"> xsd:sequence handlingInstructionCode 	<p>Occurrence 1 .. 1 Occurrence 0 .. unbounded Type ecom_common:HandlingInstructionCodeType Length 1 .. 80 Remark Information to be forwarded to the carrier, and printed on the consignment note Example Call 9110911 before delivery</p>																						
transportServiceCategoryType	<p>Occurrence 0 .. 1 Type ecom_common:TransportServiceCategoryCodeType Length 1 .. 80 Remark Transport Product Example 1020</p>																						
transportServiceLevelCode	<p>Occurrence 0 .. 1 Type ecom_common:TransportServiceLevelCodeType Length 1 .. 80 Remark Additional services, if more than one service - the codes should be separated with ; Example 1064;1060</p> <p>Applicable Codes</p> <table border="0"> <tr><td>1060</td><td>Sen innhenting</td></tr> <tr><td>1064</td><td>Varsling SMS</td></tr> <tr><td>1074</td><td>Varsling e-Mail</td></tr> <tr><td>1123</td><td>Recycling Standard</td></tr> <tr><td>1124</td><td>Installation standardised</td></tr> <tr><td>1125</td><td>Installation Customized</td></tr> <tr><td>1178</td><td>1 leveringsforsøk og deretter til hentekontor</td></tr> <tr><td>1179</td><td>2 leveringsforsøk og deretter til hentekontor</td></tr> </table>	1060	Sen innhenting	1064	Varsling SMS	1074	Varsling e-Mail	1123	Recycling Standard	1124	Installation standardised	1125	Installation Customized	1178	1 leveringsforsøk og deretter til hentekontor	1179	2 leveringsforsøk og deretter til hentekontor						
1060	Sen innhenting																						
1064	Varsling SMS																						
1074	Varsling e-Mail																						
1123	Recycling Standard																						
1124	Installation standardised																						
1125	Installation Customized																						
1178	1 leveringsforsøk og deretter til hentekontor																						
1179	2 leveringsforsøk og deretter til hentekontor																						
carrier	<p>Occurrence 0 .. 1 Type ecom_common:TransactionalPartyType</p>																						
<ul style="list-style-type: none"> xsd:sequence additionalPartyIdentification 	<p>Occurrence 1 .. 1 Occurrence 0 .. unbounded Type shared_common:AdditionalPartyIdentificationType Length 1 .. 80 Example BCI</p> <p>Applicable Codes</p> <table border="0"> <tr><td>BCI</td><td>Bring Cargo SPI</td></tr> <tr><td>BCN</td><td>Bring Cargo SPN</td></tr> <tr><td>BCS</td><td>Bring Cargo SE</td></tr> <tr><td>BDD</td><td>Bring Domestic DK</td></tr> <tr><td>BDF</td><td>Bring Domestic FI</td></tr> <tr><td>BDS</td><td>Bring Domestic SE</td></tr> <tr><td>BEX</td><td>Bring Express</td></tr> <tr><td>BFN</td><td>Bring Frigo NO</td></tr> <tr><td>BFS</td><td>Bring Frigo SE</td></tr> <tr><td>BPI</td><td>Bring Parcels AB</td></tr> <tr><td>BPN</td><td>Bring Parcels NO (former Posten No)</td></tr> </table>	BCI	Bring Cargo SPI	BCN	Bring Cargo SPN	BCS	Bring Cargo SE	BDD	Bring Domestic DK	BDF	Bring Domestic FI	BDS	Bring Domestic SE	BEX	Bring Express	BFN	Bring Frigo NO	BFS	Bring Frigo SE	BPI	Bring Parcels AB	BPN	Bring Parcels NO (former Posten No)
BCI	Bring Cargo SPI																						
BCN	Bring Cargo SPN																						
BCS	Bring Cargo SE																						
BDD	Bring Domestic DK																						
BDF	Bring Domestic FI																						
BDS	Bring Domestic SE																						
BEX	Bring Express																						
BFN	Bring Frigo NO																						
BFS	Bring Frigo SE																						
BPI	Bring Parcels AB																						
BPN	Bring Parcels NO (former Posten No)																						

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation
deliveryTerms	Occurrence 0 .. 1 Type ecom_common:DeliveryTermsType
xsd:sequence	Occurrence 1 .. 1
deliveryInstructions	Occurrence 0 .. 1 Type shared_common:Description500Type Length 1 .. 500 Remark Delivery Instructions to be handled in the WMS system and could be printed on the delivery note Example Reklamationssak Defekt kan kastas
<i>languageCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example SE
orderLinItem	Occurrence 1 .. unbounded Type order:OrderLinItem
xsd:sequence	Occurrence 1 .. 1
linItemNumber	Occurrence 1 .. 1 Type xsd:positiveInteger FractionDigits 0 Inclusive 1 .. Remark Order line number Example 1
requestedQuantity	Occurrence 1 .. 1 Type shared_common:QuantityType Remark Ordered quantity Example 21
<i>measurementUnitCode</i>	Type restriction (xsd:string) Length 1 .. 80 Example PCE Applicable Codes PCE pieces
additionalOrderLineInstruction	Occurrence 0 .. 1 Type shared_common:Description200Type Length 1 .. 200 Remark Used for text to be printed on the delivery note Example Text for delivery note
<i>languageCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example NO Applicable Codes NO
netPrice	Occurrence 0 .. 1 Type shared_common:AmountType Remark Net price Example 400
<i>currencyCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example SEK Applicable Codes SEK Swedish Crowns
monetaryAmountExcludingTaxes	Occurrence 0 .. 1 Type shared_common:AmountType Remark Price excluding VAT (Customs Value) Example 500

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
<i>currencyCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example SEK Applicable Codes SEK Swedish Crowns
note	Occurrence 0 .. 1 Type shared_common:Description500Type Length 1 .. 500 Remark Order line text Example Text...
<i>languageCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example SE Applicable Codes NO NORWAY SE SWEDEN
transactionalTradeltem	Occurrence 1 .. 1 Type ecom_common:TransactionalTradeltemType
xsd:sequence	Occurrence 1 .. 1
gtin	Occurrence 1 .. 1 Type shared_common:GTINType Pattern \d{14} Remark GTIN13 (GS1 Article number) Example 0731087000888
additionalTradeltemIdentification	Occurrence 0 .. unbounded Type shared_common:AdditionalTradeltemIdentificationType Length 1 .. 80 Remark Suppliers article number Example 123456 Remark Customer Order number Example 67-134-0 Remark Free Text - information for delivery note Example RE-TEST-
<i>additionalTradeltemIdentificationTypeCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example SA Example ON Example ZFX Applicable Codes ON Customer Order Number SA Supplier's article number ZFX Free Text
xsd:sequence	Occurrence 1 .. 1
tradeltemDescription	Occurrence 0 .. 1 Type shared_common:Description200Type Length 1 .. 200 Remark Item description Example apple cake
<i>languageCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example SE

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
-------------------	------------

Applicable Codes	
------------------	--

NO	NORWAY
SE	SWEDEN

```

<?xml version="1.0" encoding="UTF-8" ?>
- <order:orderMessage xmlns:order="urn:gs1:ecom:order:xsd:3"
  xmlns:sh="http://www.unece.org/cefact/namespaces/StandardBusinessDocumentHeader">
- <sh:StandardBusinessDocumentHeader>
- <sh:HeaderVersion>3.1</sh:HeaderVersion>
- <sh:Sender>
- <sh:Identifier Authority="ZZ">567819</sh:Identifier>
- </sh:Sender>
- <sh:Receiver>
- <sh:Identifier Authority="14">7393321400011</sh:Identifier>
- </sh:Receiver>
- <sh:DocumentIdentification>
- <sh:Standard>GS1 BMS</sh:Standard>
- <sh:TypeVersion>3.1</sh:TypeVersion>
- <sh:InstanceIdentifier>GS1</sh:InstanceIdentifier>
- <sh:Type>Orders</sh:Type>
- <sh:CreationDateAndTime>2015-02-02T12:10:00</sh:CreationDateAndTime>
- </sh:DocumentIdentification>
- </sh:StandardBusinessDocumentHeader>
- <order>
- <creationDateTime>2015-02-02T12:10:00</creationDateTime>
- <documentStatusCode>ORIGINAL</documentStatusCode>
- <orderIdentification>
- <entityIdentification>125987</entityIdentification>
- </orderIdentification>
- <orderTypeCode>220</orderTypeCode>
- <orderInstructionCode>S</orderInstructionCode>
- <additionalOrderInstruction languageCode="NO">00</additionalOrderInstruction>
- <note languageCode="NO">69581A</note>
- <buyer>
- <gln>7356099100013</gln>
- <additionalPartyIdentification
  additionalPartyIdentificationTypeCode="88">50214</additionalPartyIdentification>
- </buyer>
- <seller>
- <gln>7356099100013</gln>
- <additionalPartyIdentification
  additionalPartyIdentificationTypeCode="88">456783</additionalPartyIdentification>
- </seller>
- <orderLogisticalInformation>
- <shipTo>
- <gln>7310500001005</gln>
- <additionalPartyIdentification
  additionalPartyIdentificationTypeCode="88">50296</additionalPartyIdentification>
- <address>
- <city>Höganäs</city>
- <countryCode>SE</countryCode>
- <name>ICA Kvantum</name>
- <postalCode>26005</postalCode>
- <streetAddressOne>Köpmansgatan 10</streetAddressOne>
- <streetAddressTwo>Adress rad 2</streetAddressTwo>
- </address>
- <contact>
- <communicationChannel>
- <communicationChannelCode>EM</communicationChannelCode>
- <communicationValue>test.testsson@test.te</communicationValue>

```

Bold = Element, Italic = Attribute, Grey = Group

```

    </communicationChannel>
    </contact>
    </shipTo>
- <inventoryLocation>
  <gln>7393321401018</gln>
  <additionalPartyIdentification
    additionalPartyIdentificationTypeCode="88">BERGER</additionalPartyIdentification>
  </inventoryLocation>
- <orderLogisticalDateInformation>
- <requestedDeliveryDateRange>
  <beginDate>2015-06-20</beginDate>
  <beginTime>12:00:00</beginTime>
  <endDate>2015-06-20</endDate>
  <endTime>16:00:00</endTime>
  </requestedDeliveryDateRange>
- <requestedDeliveryDateTime>
  <date>2014-10-01</date>
  <time>14:00:00</time>
  </requestedDeliveryDateTime>
  </orderLogisticalDateInformation>
- <shipmentTransportationInformation>
  <handlingInstructionCode>Call 9110911 before delivery</handlingInstructionCode>
  <transportServiceCategoryType>1020</transportServiceCategoryType>
  <transportServiceLevelCode>1064;1060</transportServiceLevelCode>
- <carrier>
  <additionalPartyIdentification
    additionalPartyIdentificationTypeCode="87">BCI</additionalPartyIdentification>
  </carrier>
  </shipmentTransportationInformation>
  </orderLogisticalInformation>
- <deliveryTerms>
  <deliveryInstructions languageCode="SE">Reklamations sak Defekt kan
    kastas</deliveryInstructions>
  </deliveryTerms>
- <orderLineItem>
  <lineItemNumber>1</lineItemNumber>
  <requestedQuantity measurementUnitCode="PCE">21</requestedQuantity>
  <additionalOrderLineInstruction languageCode="NO">Text for delivery
    note</additionalOrderLineInstruction>
  <netPrice currencyCode="SEK">400</netPrice>
  <monetaryAmountExcludingTaxes currencyCode="SEK">500</monetaryAmountExcludingTaxes>
  <note languageCode="SE">Text....</note>
- <transactionalTradeItem>
  <gtin>07310870008888</gtin>
  <additionalTradeItemIdentification
    additionalTradeItemIdentificationTypeCode="SA">123456</additionalTradeItemIdentification>
  <additionalTradeItemIdentification
    additionalTradeItemIdentificationTypeCode="ON">67-134-0</additionalTradeItemIdentification>
  <additionalTradeItemIdentification
    additionalTradeItemIdentificationTypeCode="ZFX">RE-TEST-</additionalTradeItemIdentification
  >
  <tradeItemDescription languageCode="SE">apple cake</tradeItemDescription>
  </transactionalTradeItem>
  </orderLineItem>
  </order>
  </order:orderMessage>

```

Bold = Element, Italic = Attribute, Grey = Group



Bold = Element, Italic = Attribute, Grey = Group