



Message Implementation Guideline

Customer Orders XML

Model: Customer Order
Version: GS1 BMB 3.1
Variant: 20
Issue date: 03.04.2019
Author: Vidar Thoresen

1 Structure	3
2 Guideline	9

Change log Customer Order

Date	Variant	Comments
08.04.2019	20	Merged GS1 3.1 for Axia and Nyce systems

Structure

Occurrence	Element/Attribute
	orderMessage
1 .. 1	xsd:sequence
1 .. 1	sh:StandardBusinessDocumentHeader
1 .. 1	xs:sequence
1 .. 1	HeaderVersion
1 .. unbounded	Sender
1 .. 1	xs:sequence
1 .. 1	Identifier
	<i>Authority</i>
0 .. unbounded	ContactInformation
1 .. unbounded	Receiver
1 .. 1	xs:sequence
1 .. 1	Identifier
	<i>Authority</i>
0 .. unbounded	ContactInformation
1 .. 1	DocumentIdentification
1 .. 1	xs:sequence
1 .. 1	Standard
1 .. 1	TypeVersion
1 .. 1	InstancelIdentifier
1 .. 1	Type
0 .. 1	MultipleType
1 .. 1	CreationDateAndTime
0 .. 1	Manifest
0 .. 1	BusinessScope
1 .. 10000	order
1 .. 1	xsd:sequence
1 .. 1	creationDateTime
1 .. 1	documentStatusCode
0 .. 1	documentActionCode
0 .. 1	documentStructureVersion
0 .. 1	lastUpdateDateTime
0 .. 1	revisionNumber
0 .. 1	extension
0 .. 1	documentEffectiveDate
1 .. 1	xsd:sequence
1 .. 1	orderIdentification
1 .. 1	xs:sequence
1 .. 1	entityIdentification
0 .. 1	contentOwner
0 .. 1	orderTypeCode
	<i>codeListVersion</i>
0 .. 1	isApplicationReceiptAcknowledgementRequired
1 .. 1	orderInstructionCode
	<i>codeListVersion</i>
0 .. 1	additionalOrderInstruction
required	<i>languageCode</i>
	<i>codeListVersion</i>

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
0 .. 1	isOrderFreeOfExciseTaxDuty
0 .. 1	totalMonetaryAmountExcludingTaxes
0 .. 1	totalMonetaryAmountIncludingTaxes
0 .. 1	totalTaxAmount
0 .. 1	note
required	languageCode
	codeListVersion
1 .. 1	buyer
1 .. 1	xsd:sequence
0 .. 1	gln
0 .. unbounded	additionalPartyIdentification
required	additionalPartyIdentificationTypeCode
	codeListVersion
0 .. 1	address
0 .. unbounded	contact
1 .. 1	xsd:sequence
0 .. 1	contactTypeCode
0 .. 1	personName
0 .. 1	departmentName
0 .. 1	jobTitle
0 .. unbounded	responsibility
0 .. unbounded	communicationChannel
0 .. unbounded	afterHoursCommunicationChannel
0 .. unbounded	dutyFeeTaxRegistration
0 .. 1	organisationDetails
0 .. unbounded	financialInstitutionInformation
1 .. 1	seller
1 .. 1	xsd:sequence
0 .. 1	gln
0 .. unbounded	additionalPartyIdentification
required	additionalPartyIdentificationTypeCode
	codeListVersion
0 .. 1	address
0 .. unbounded	contact
1 .. 1	xsd:sequence
0 .. 1	contactTypeCode
0 .. 1	personName
0 .. 1	departmentName
0 .. 1	jobTitle
0 .. unbounded	responsibility
0 .. unbounded	communicationChannel
0 .. unbounded	afterHoursCommunicationChannel
0 .. unbounded	dutyFeeTaxRegistration
0 .. 1	organisationDetails
0 .. unbounded	financialInstitutionInformation
0 .. 1	billTo
1 .. 1	orderLogisticalInformation
1 .. 1	xsd:sequence
0 .. 1	shipFrom

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
0 .. 1	shipTo
1 .. 1	xsd:sequence
0 .. 1	gln
0 .. unbounded required	additionalPartyIdentification
	<i>additionalPartyIdentificationTypeCode</i>
	<i>codeListVersion</i>
0 .. 1	address
1 .. 1	xsd:sequence
0 .. 1	city
0 .. 1	cityCode
0 .. 1	countryCode
	<i>codeListVersion</i>
0 .. 1	countyCode
0 .. 1	crossStreet
0 .. 1	currencyOfPartyCode
0 .. 1	languageOfThePartyCode
0 .. 1	name
0 .. 1	pOBoxNumber
0 .. 1	postalCode
0 .. 1	provinceCode
0 .. 1	state
0 .. 1	streetAddressOne
0 .. 1	streetAddressTwo
0 .. 1	streetAddressThree
0 .. 1	geographicalCoordinates
0 .. unbounded	contact
1 .. 1	xsd:sequence
0 .. 1	contactTypeCode
0 .. 1	personName
0 .. 1	departmentName
0 .. 1	jobTitle
0 .. unbounded	responsibility
0 .. unbounded	communicationChannel
1 .. 1	xsd:sequence
1 .. 1	communicationChannelCode
	<i>codeListVersion</i>
1 .. 1	communicationValue
0 .. 1	communicationChannelName
0 .. unbounded	afterHoursCommunicationChannel
0 .. unbounded	dutyFeeTaxRegistration
0 .. 1	organisationDetails
0 .. unbounded	financialInstitutionInformation
1 .. 1	inventoryLocation
1 .. 1	xsd:sequence
0 .. 1	gln
1 .. 1	additionalPartyIdentification
required	<i>additionalPartyIdentificationTypeCode</i>
	<i>codeListVersion</i>
0 .. 1	address
0 .. unbounded	contact
	dutyFeeTaxRegistration

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
0 .. unbounded	
0 .. 1	organisationDetails
0 .. unbounded	financialInstitutionInformation
0 .. 1	ultimateConsignee
0 .. 1	orderLogisticalDateInformation
1 .. 1	xsd:sequence
0 .. 1	requestedDeliveryDateRange
1 .. 1	xsd:sequence
0 .. 1	beginDate
0 .. 1	beginTime
0 .. 1	endDate
0 .. 1	endTime
0 .. 1	requestedShipDateRange
0 .. 1	requestedDeliveryDateRangeAtUltimateConsignee
0 .. 1	requestedDeliveryDateTime
1 .. 1	xsd:sequence
1 .. 1	date
0 .. 1	time
0 .. 1	requestedShipDateTime
0 .. 1	requestedPickUpDateTime
0 .. 1	requestedDeliveryDateTimeAtUltimateConsignee
0 .. 1	shipmentTransportationInformation
1 .. 1	xsd:sequence
0 .. unbounded	handlingInstructionCode
	codeListVersion
0 .. 1	transportMeansType
0 .. 1	transportServiceCategoryType
	codeListVersion
0 .. 1	transportServiceLevelCode
	codeListVersion
0 .. 1	carrier
1 .. 1	xsd:sequence
0 .. 1	gln
0 .. unbounded	additionalPartyIdentification
required	additionalPartyIdentificationTypeCode
	codeListVersion
0 .. 1	address
0 .. unbounded	contact
0 .. unbounded	dutyFeeTaxRegistration
0 .. 1	organisationDetails
0 .. unbounded	financialInstitutionInformation
0 .. 1	freightForwarder
0 .. unbounded	paymentTerms
0 .. unbounded	allowanceCharge
0 .. 1	tradeAgreement
0 .. 1	promotionalDeal
0 .. 1	quoteNumber
0 .. 1	currencyExchangeRateInformation

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
0 .. 1	deliveryTerms
1 .. 1	xsd:sequence
0 .. 1	incotermsCode
	<i>codeListVersion</i>
0 .. 1	alternateDeliveryTermsCode
0 .. 1	deliveryInstructions
required	<i>languageCode</i>
	<i>codeListVersion</i>
0 .. 1	deliveryTermsLocation
1 .. unbounded	orderLineItem
1 .. 1	xsd:sequence
1 .. 1	lineItemNumber
1 .. 1	requestedQuantity
	<i>measurementUnitCode</i>
	<i>codeListVersion</i>
0 .. 1	lineItemActionCode
0 .. 1	additionalOrderLineInstruction
required	<i>languageCode</i>
	<i>codeListVersion</i>
0 .. 1	netAmount
0 .. 1	netPrice
required	<i>currencyCode</i>
	<i>codeListVersion</i>
0 .. 1	monetaryAmountExcludingTaxes
required	<i>currencyCode</i>
	<i>codeListVersion</i>
0 .. 1	monetaryAmountIncludingTaxes
0 .. 1	note
required	<i>languageCode</i>
	<i>codeListVersion</i>
1 .. 1	transactionalTradeItem
1 .. 1	xsd:sequence
1 .. 1	gtin
0 .. unbounded	additionalTradeItemIdentification
required	<i>additionalTradeItemIdentificationTypeCode</i>
	<i>codeListVersion</i>
1 .. 1	xsd:sequence
0 .. 1	tradeItemQuantity
0 .. 1	tradeItemDescription
required	<i>languageCode</i>
	<i>codeListVersion</i>
0 .. 1	productVariantIdentifier
0 .. unbounded	transactionalItemData
0 .. unbounded	colour
0 .. unbounded	size
0 .. unbounded	allowanceCharge
0 .. 1	shipmentTransportationInformation
0 .. 1	promotionalDeal
0 .. 1	purchaseConditions
1 .. 1	xsd:sequence
1 .. 1	entityIdentification

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
0 .. 1	contentOwner
1 .. 1	xsd:sequence
0 .. 1	creationDateTime
0 .. 1	revisionNumber
0 .. 1	lineltemNumber
0 .. 1	materialSpecification
0 .. 1	leviedDutyFeeTax
0 .. unbounded	orderLineltemDetail

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Guideline

Element/Attribute	Annotation
orderMessage	Type order:OrderMessageType
xsd:sequence	Occurrence 1 .. 1
sh:StandardBusinessDocumentHeader	Occurrence 1 .. 1 Type sh:StandardBusinessDocumentHeader
xsd:sequence	Occurrence 1 .. 1
HeaderVersion	Occurrence 1 .. 1 Type xsd:string Example 3.1
Sender	Occurrence 1 .. unbounded Type sh:Partner
xsd:sequence	Occurrence 1 .. 1
Identifier	Occurrence 1 .. 1 Type sh:PartnerIdentification Remark Client Id - to be agreed Example 567819
<i>Authority</i>	Type xsd:string Example ZZ
	Applicable Codes
	14 EAN International
	30 ISO 6523: Organization identification
	ZZ Mutually defined
Receiver	Occurrence 1 .. unbounded Type sh:Partner
xsd:sequence	Occurrence 1 .. 1
Identifier	Occurrence 1 .. 1 Type sh:PartnerIdentification Remark GLN (GS1 location code) for receiver of the message - to be agreed Example 7080000950171
<i>Authority</i>	Type xsd:string Example 14
	Applicable Codes
	14 EAN International
	30 ISO 6523: Organization identification
	ZZ Mutually defined
DocumentIdentification	Occurrence 1 .. 1 Type sh:DocumentIdentification
xsd:sequence	Occurrence 1 .. 1
Standard	Occurrence 1 .. 1 Type xsd:string Example GS1 BMS
TypeVersion	Occurrence 1 .. 1 Type xsd:string Example 3.1
InstanceIdentifier	Occurrence 1 .. 1 Type xsd:string Example GS1
Type	Occurrence 1 .. 1 Type xsd:string Example Orders
CreationDateAndTime	Occurrence 1 .. 1 Type xsd:dateTime Remark message date/time Example 2015-02-02T12:10:00

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
order	<p>Occurrence 1 .. 10000</p> <p>Type order:OrderType</p>
xsd:sequence	Occurrence 1 .. 1
creationDateTime	<p>Occurrence 1 .. 1</p> <p>Type xsd:dateTime</p> <p>Remark Document date/time</p> <p>Example 2015-02-02T12:10:00</p>
documentStatusCode	<p>Occurrence 1 .. 1</p> <p>Type shared_common:DocumentStatusEnumerationType</p> <p>Remark Function</p> <p>Applicable Codes</p> <p>ORIGINAL</p>
documentActionCode	<p>Occurrence 0 .. 1</p> <p>Type shared_common:DocumentActionEnumerationType</p>
xsd:sequence	Occurrence 1 .. 1
orderIdentification	<p>Occurrence 1 .. 1</p> <p>Type shared_common:EntityIdentificationType</p>
xsd:sequence	Occurrence 1 .. 1
entityIdentification	<p>Occurrence 1 .. 1</p> <p>Type restriction (xsd:string)</p> <p>Length 1 .. 35</p> <p>Remark Ordernumber</p> <p>Example 125987</p>
orderTypeCode	<p>Occurrence 0 .. 1</p> <p>Type ecom_common:OrderTypeCodeType</p> <p>Length 1 .. 80</p> <p>Description 224 (Rush Order) only used by Bring Warehousing</p> <p>Example 220</p> <p>Applicable Codes</p> <p>220 Order</p> <p>224 Rush order</p>
isApplicationReceiptAcknowledgementRequired	<p>Occurrence 0 .. 1</p> <p>Type xsd:boolean</p>
orderInstructionCode	<p>Occurrence 1 .. 1</p> <p>Type ecom_common:OrderInstructionCodeType</p> <p>Length 1 .. 80</p> <p>Remark InstructionCode</p> <p>Example S</p> <p>Remark Picking Zone</p> <p>Example outbound_standard</p> <p>Remark DocumentNumber</p> <p>Example 33</p> <p>Remark Priority</p> <p>Example 2</p> <p>Applicable Codes</p> <p>0 Priority 0</p> <p>1 Priority 1</p> <p>2 Priority 2</p> <p>3 Priority 3</p> <p>4 Priority 4</p> <p>5 Priority 5</p> <p>6 Priority 6</p> <p>C Cutting (Norway)</p> <p>N Normal (Norway)</p> <p>S Sampakk (Norway)</p> <p>outbound_standard Picking Zone (Sweden / Finland)</p>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
<i>codeListVersion</i>	Type restriction (xsd:string) Length 1 .. 35 Applicable Codes Discount DocumentNumber InstructionCode PickingZone Priority
additionalOrderInstruction	Occurrence 0 .. 1 Type shared_common:Description1000Type Length 1 .. 1000 Remark Additional information to the Warehouse - as Shipping Conditions Example 02 Remark Allow Partial delivery Example true Applicable Codes 02 Shipping Conditions false Not allow partial delivery true Allow partial delivery
<i>languageCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example NO Applicable Codes NO Norway SE Sweden
<i>codeListVersion</i>	Type restriction (xsd:string) Length 1 .. 35 Applicable Codes AllowPartialDelivery Allow Partial delivery ShippingConditions Shipping conditions
note	Occurrence 0 .. 1 Type shared_common:Description500Type Length 1 .. 500 Remark Consignor's or additional reference number Example 69581A
<i>languageCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example NO Applicable Codes NO
buyer	Occurrence 1 .. 1 Type ecom_common:TransactionalPartyType
xsd:sequence	Occurrence 1 .. 1
gln	Occurrence 0 .. 1 Type shared_common:GLNType Pattern \d{13} Remark GLN (GS1 location code) for buyer Example 7356099100013
additionalPartyIdentification	Occurrence 0 .. unbounded Type shared_common:AdditionalPartyIdentificationType Length 1 .. 80 Remark Customer id assigned by Bring and additionalPartyIdentificationTypeCode = '88'

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
<i>additionalPartyIdentificationTypeCode</i>	<p>Example 50214</p> <p>Type restriction (xsd:string)</p> <p>Length 1 .. 80</p> <p>Use required</p> <p>Example 88</p> <p>Applicable Codes</p> <p>87 Assigned by carrier</p> <p>88 Assigned by the owner of operation</p>
contact	<p>Occurrence 0 .. unbounded</p> <p>Type shared_common:ContactType</p>
xsd:sequence	<p>Occurrence 1 .. 1</p>
personName	<p>Occurrence 0 .. 1</p> <p>Type restriction (xsd:string)</p> <p>Length 1 .. 70</p>
communicationChannel	<p>Occurrence 0 .. unbounded</p> <p>Type shared_common:CommunicationChannelType</p>
seller	<p>Occurrence 1 .. 1</p> <p>Type ecom_common:TransactionalPartyType</p>
xsd:sequence	<p>Occurrence 1 .. 1</p>
gln	<p>Occurrence 0 .. 1</p> <p>Type shared_common:GLNType</p> <p>Pattern \d{13}</p> <p>Remark GLN for supplier</p> <p>Example 7356099100013</p>
additionalPartyIdentification	<p>Occurrence 0 .. unbounded</p> <p>Type shared_common:AdditionalPartyIdentificationType</p> <p>Length 1 .. 80</p> <p>Remark Customer id assigned by Bring and additionalPartyIdentificationTypeCode = '88'</p> <p>Example 456783</p>
<i>additionalPartyIdentificationTypeCode</i>	<p>Type restriction (xsd:string)</p> <p>Length 1 .. 80</p> <p>Use required</p> <p>Example 88</p> <p>Applicable Codes</p> <p>88 Assigned by the owner of operation</p>
contact	<p>Occurrence 0 .. unbounded</p> <p>Type shared_common:ContactType</p>
xsd:sequence	<p>Occurrence 1 .. 1</p>
personName	<p>Occurrence 0 .. 1</p> <p>Type restriction (xsd:string)</p> <p>Length 1 .. 70</p>
communicationChannel	<p>Occurrence 0 .. unbounded</p> <p>Type shared_common:CommunicationChannelType</p>
orderLogisticalInformation	<p>Occurrence 1 .. 1</p> <p>Type ecom_common:OrderLogisticalInformationType</p>
xsd:sequence	<p>Occurrence 1 .. 1</p>
shipTo	<p>Occurrence 0 .. 1</p> <p>Type ecom_common:TransactionalPartyType</p>
xsd:sequence	<p>Occurrence 1 .. 1</p>
gln	<p>Occurrence 0 .. 1</p> <p>Type shared_common:GLNType</p> <p>Pattern \d{13}</p> <p>Remark GLN for delivery party</p> <p>Example 7310500001005</p>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
additionalPartyIdentification	Occurrence 0 .. unbounded Type shared_common:AdditionalPartyIdentificationType Length 1 .. 80 Remark Customer id for delivery party Example 50296
<i>additionalPartyIdentificationTypeCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example 88 Applicable Codes 87 Assigned by carrier 88 Assigned by the owner of operation
address	Occurrence 0 .. 1 Type shared_common:AddressType
<i>xsd:sequence</i>	Occurrence 1 .. 1
city	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 200 Remark Ship to party city name Example Höganäs
countryCode	Occurrence 0 .. 1 Type shared_common:CountryCodeType Length 1 .. 80 Remark ISO 3166 alpha Example SE
name	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 200 Remark Ship to party name Example ICA Kvantum
postalCode	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 80 Remark Ship to postal code Example 26005
streetAddressOne	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 200 Remark Ship to, Street adress Example Köpmansgatan 10
streetAddressTwo	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 200 Example Adress rad 2
contact	Occurrence 0 .. unbounded Type shared_common:ContactType
<i>xsd:sequence</i>	Occurrence 1 .. 1
communicationChannel	Occurrence 0 .. unbounded Type shared_common:CommunicationChannelType
<i>xsd:sequence</i>	Occurrence 1 .. 1
communicationChannelCode	Occurrence 1 .. 1 Type shared_common:CommunicationChannelCodeType Length 1 .. 80 Example EM Applicable Codes EM Electronic mail

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	Applicable Codes
	TE Telephone
	ZM Mobile phone number
communicationValue	Occurrence 1 .. 1 Type restriction (xsd:string) Length 1 .. 200 Remark E-mail address / Telephone number Example test.testsson@test.te
inventoryLocation	Occurrence 1 .. 1 Type ecom_common:TransactionalPartyType
xsd:sequence	Occurrence 1 .. 1
gln	Occurrence 0 .. 1 Type shared_common:GLNType Pattern \d{13} Remark GLN for Warehouse location Example 7393321401018
additionalPartyIdentification	Occurrence 1 .. 1 Type shared_common:AdditionalPartyIdentificationType Length 1 .. 80 Remark Warehouse location assigned by the owner of the operation Example BERGER
	Applicable Codes
	4033 Stavanger (Norway)
	5500 Haugesund (Norway)
	AES Ålesund (Norway)
	BERGER Berger/Skedsмокorset (Norway)
	BS02 Kongshavn (Norway)
	BS07 Trollåsen (Norway)
	BS17 Bergen (Norway)
	BS26 Trondheim (Norway)
	BS34 Tromsø (Norway)
	FI01 Finland
	JKPG01 Jönköping (Sweden)
	NCD Lierstrand (Norway)
additionalPartyIdentificationTypeCode	Type restriction (xsd:string) Length 1 .. 80 Use required Example 88
	Applicable Codes
	88 Assigned by the owner of operation
orderLogisticalDateInformation	Occurrence 0 .. 1 Type ecom_common:OrderLogisticalDateInformationType
xsd:sequence	Occurrence 1 .. 1
requestedDeliveryDateRange	Occurrence 0 .. 1 Type shared_common:DateTimeRangeType
xsd:sequence	Occurrence 1 .. 1
beginDate	Occurrence 0 .. 1 Type xsd:date Remark Requested delivery date start (CCYY-MM-DD) Example 2015-06-20
beginTime	Occurrence 0 .. 1 Type xsd:time Remark Requested delivery time start (HH:MM:SS) Example 12:00:00

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
<ul style="list-style-type: none"> endDate 	<p>Occurrence 0 .. 1 Type xsd:date Remark Requested delivery date end (CCYY-MM-DD) Example 2015-06-20</p>
<ul style="list-style-type: none"> endTime 	<p>Occurrence 0 .. 1 Type xsd:time Remark Requested delivery time start (HH:MM:SS) Example 16:00:00</p>
<ul style="list-style-type: none"> requestedDeliveryDateTime 	<p>Occurrence 0 .. 1 Type shared_common:DateOptionalTimeType Remark Delivery date at customers site</p>
<ul style="list-style-type: none"> xsd:sequence <ul style="list-style-type: none"> date 	<p>Occurrence 1 .. 1 Occurrence 1 .. 1 Type xsd:date Remark Delivery date at customers site (YYYY-MM-DD) Example 2014-10-01</p>
<ul style="list-style-type: none"> time 	<p>Occurrence 0 .. 1 Type xsd:time Remark Delivery time customers siteTime (HH:MM:SS) Example 14:00:00</p>
shipmentTransportationInformation	<p>Occurrence 0 .. 1 Type ecom_common:ShipmentTransportationInformationType</p>
<ul style="list-style-type: none"> xsd:sequence <ul style="list-style-type: none"> handlingInstructionCode 	<p>Occurrence 0 .. unbounded Type ecom_common:HandlingInstructionCodeType Length 1 .. 80 Remark Information to be forwarded to the carrier, and printed on the consignment note Example Call 9110911 before delivery</p>
transportServiceCategoryType	<p>Occurrence 0 .. 1 Type ecom_common:TransportServiceCategoryCodeType Length 1 .. 80 Remark Transport Product Example 1020</p>
transportServiceLevelCode	<p>Occurrence 0 .. 1 Type ecom_common:TransportServiceLevelCodeType Length 1 .. 80 Remark Additional services, if more than one service - the codes should be separated with ; Example 1064;1060</p>
Applicable Codes	
1060	Sen innhenting
1064	Varsling SMS
1074	Varsling e-Mail
1123	Recycling Standard
1124	Installation standardised
1125	Installation Customized
1178	1 leveringsforsøk og deretter til hentekontor
1179	2 leveringsforsøk og deretter til hentekontor
carrier	<p>Occurrence 0 .. 1 Type ecom_common:TransactionalPartyType</p>
<ul style="list-style-type: none"> xsd:sequence <ul style="list-style-type: none"> additionalPartyIdentification 	<p>Occurrence 1 .. 1 Occurrence 0 .. unbounded Type shared_common:AdditionalPartyIdentificationType Length 1 .. 80</p>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	<p>Example BCI</p> <p>Applicable Codes</p> <p>BCI Bring Cargo SPI BCN Bring Cargo SPN BCS Bring Cargo SE BDD Bring Domestic DK BDF Bring Domestic FI BDS Bring Domestic SE BEX Bring Express BFN Bring Frigo NO BFS Bring Frigo SE BPI Bring Parcels AB BPN Bring Parcels NO (former Posten No)</p>
<i>additionalPartyIdentificationCode</i>	<p>Type restriction (xsd:string) Length 1 .. 80 Use required Example 87</p> <p>Applicable Codes</p> <p>87 Assigned by carrier</p>
deliveryTerms	<p>Occurrence 0 .. 1 Type ecom_common:DeliveryTermsType</p>
<i>xsd:sequence</i>	<p>Occurrence 1 .. 1</p>
incotermsCode	<p>Occurrence 0 .. 1 Type shared_common:IncotermsCodeType Length 1 .. 80 Remark Incoterms Example EXW</p> <p>Applicable Codes</p> <p>DDP Delivered Duty Paid (... named place of destination) EXW Ex Works (... named place)</p>
deliveryInstructions	<p>Occurrence 0 .. 1 Type shared_common:Description500Type Length 1 .. 500 Remark Delivery Instructions to be handled in the WMS system and could be printed on the delivery note Example Reklamationssak Defekt kan kastas</p>
<i>languageCode</i>	<p>Type restriction (xsd:string) Length 1 .. 80 Use required Example SE</p>
orderLineItem	<p>Occurrence 1 .. unbounded Type order:OrderLineItemType</p>
<i>xsd:sequence</i>	<p>Occurrence 1 .. 1</p>
lineItemNumber	<p>Occurrence 1 .. 1 Type xsd:positiveInteger FractionDigits 0 Inclusive 1 .. Remark Order line number Example 1</p>
requestedQuantity	<p>Occurrence 1 .. 1 Type shared_common:QuantityType Remark Ordered quantity Example 21</p>
<i>measurementUnitCode</i>	<p>Type restriction (xsd:string) Length 1 .. 80 Example PCE</p>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	Applicable Codes
	PCE pieces
additionalOrderLineInstruction	Occurrence 0 .. 1 Type shared_common:Description200Type Length 1 .. 200 Remark Used for text to be printed on the delivery note Example Text for delivery note
<i>languageCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example NO
	Applicable Codes
	NO
netPrice	Occurrence 0 .. 1 Type shared_common:AmountType Remark Net price Example 400
<i>currencyCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example NOK
	Applicable Codes
	DKK Danish Crowns EUR Euro NOK Norwegian Crowns SEK Swedish Crowns
monetaryAmountExcludingTaxes	Occurrence 0 .. 1 Type shared_common:AmountType Remark Price excluding VAT (Customs Value) Example 500
<i>currencyCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example NOK
	Applicable Codes
	NOK Norwegian Crowns
note	Occurrence 0 .. 1 Type shared_common:Description500Type Length 1 .. 500 Remark Order line text Example Text...
<i>languageCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example SE
	Applicable Codes
	NO NORWAY SE SWEDEN
transactionalTradeltem	Occurrence 1 .. 1 Type ecom_common:TransactionalTradeltemType
<i>xsd:sequence</i>	Occurrence 1 .. 1
gtin	Occurrence 1 .. 1 Type shared_common:GTINType Pattern \d{14} Remark GTIN13 (GS1 Article number) Example 07310870008888

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
additionalTradeltemIdentification	Occurrence 0 .. unbounded Type shared_common:AdditionalTradeltemIdentificationType Length 1 .. 80 Remark Suppliers article number Example 123456 Remark Customer Order number Example 67-134-0 Remark Free Text - information for delivery note Example RE-TEST-
<i>additionalTradeltemIdentificationTypeCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example SA Example ON Example ZFX
Applicable Codes	
ON	Customer Order Number
SA	Supplier's article number
ZDS	Discount
ZFX	Free Text
ZGR	Grade
ZMSRP	Market Suggested Retail Price
xsd:sequence	Occurrence 1 .. 1
tradeltemDescription	Occurrence 0 .. 1 Type shared_common:Description200Type Length 1 .. 200 Remark Item description Example apple cake
<i>languageCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example SE
Applicable Codes	
NO	NORWAY
SE	SWEDEN
productVariantIdentifier	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 80
purchaseConditions	Occurrence 0 .. 1 Type shared_common:DocumentReferenceType
xsd:sequence	Occurrence 1 .. 1
entityIdentification	Occurrence 1 .. 1 Type restriction (xsd:string) Length 1 .. 80 Remark Reference to purchase order number for this order Example 6CE65B05BE09A
xsd:sequence	Occurrence 1 .. 1
lineItemNumber	Occurrence 0 .. 1 Type xsd:positiveInteger FractionDigits 0 Inclusive 1 .. Remark Line item number on purchase order Example 1

Bold = Element, *Italic* = Attribute, Grey = Group

```

<?xml version="1.0" encoding="UTF-8"?>
<ns0:orderMessage xmlns:ns0="urn:gs1:ecom:order:xsd:3">
  <ns1:StandardBusinessDocumentHeader
xmlns:ns1="http://www.unece.org/cefact/namespaces/StandardBusinessDocumentHeader">
  <ns1:HeaderVersion>3.1</ns1:HeaderVersion>
  <ns1:Sender>
    <ns1:Identifier Authority="14">999999</ns1:Identifier>
  </ns1:Sender>
  <ns1:Receiver>
    <ns1:Identifier Authority="14">7080003388100</ns1:Identifier>
  </ns1:Receiver>
  <ns1:DocumentIdentification>
    <ns1:Standard>GS1 BMS</ns1:Standard>
    <ns1:TypeVersion>3.1</ns1:TypeVersion>
    <ns1:InstanceIdentifier>GS1</ns1:InstanceIdentifier>
    <ns1:Type>Orders</ns1:Type>
    <ns1:CreationDateAndTime>2019-03-26T18:36:48</ns1:CreationDateAndTime>
  </ns1:DocumentIdentification>
</ns1:StandardBusinessDocumentHeader>
<order>
  <creationDateTime>2019-03-26T18:38:01</creationDateTime>
  <documentStatusCode>ORIGINAL</documentStatusCode>
  <orderIdentification>
    <entityIdentification>81201513</entityIdentification>
  </orderIdentification>
  <orderTypeCode>220</orderTypeCode>
  <orderInstructionCode>N</orderInstructionCode>
  <buyer>
    <additionalPartyIdentification
additionalPartyIdentificationTypeCode="88">999999</additionalPartyIdentification>
    <contact>
      <personName>BuyerName</personName>
    </contact>
  </buyer>
  <seller>
    <additionalPartyIdentification
additionalPartyIdentificationTypeCode="88">999999</additionalPartyIdentification>
    <contact>
      <personName>SellerName</personName>
    </contact>
  </seller>
  <orderLogisticalInformation>
    <shipTo>
      <additionalPartyIdentification
additionalPartyIdentificationTypeCode="88">999999</additionalPartyIdentification>
      <address>
        <city>CityTest</city>
        <countryCode>NO</countryCode>
        <name>Ship-toNavn</name>
        <postalCode>0000</postalCode>
        <streetAddressOne>Streetaddress_line1</streetAddressOne>
        <streetAddressTwo>Streetaddress_line2</streetAddressTwo>
      </address>
      <contact>
        <communicationChannel>

```

Bold = Element, *Italic* = Attribute, Grey = Group

```

        <communicationChannelCode>TE</communicationChannelCode>
        <communicationValue>12345678</communicationValue>
    </communicationChannel>
</contact>
</shipTo>
<inventoryLocation>
    <additionalPartyIdentification
additionalPartyIdentificationTypeCode="88">BS02</additionalPartyIdentification>
    </inventoryLocation>
    <orderLogisticalDateInformation>
        <requestedDeliveryDateTime>
            <date>2019-03-25</date>
        </requestedDeliveryDateTime>
    </orderLogisticalDateInformation>
    <shipmentTransportationInformation>
        <handlingInstructionCode>Instructions_Call 30 minutes before delivery</handlingInstructionCode>
        <handlingInstructionCode>Instructions_SecondLine</handlingInstructionCode>
        <transportServiceCategoryType>3270</transportServiceCategoryType>
        <carrier>
            <additionalPartyIdentification
additionalPartyIdentificationTypeCode="87">E81</additionalPartyIdentification>
        </carrier>
    </shipmentTransportationInformation>
</orderLogisticalInformation>
<orderLineItem>
    <lineItemNumber>10</lineItemNumber>
    <requestedQuantity measurementUnitCode="PCE">5.00</requestedQuantity>
    <transactionalTradeItem>
        <gtin>7613023191650</gtin>
        <additionalTradeItemIdentification
additionalTradeItemIdentificationTypeCode="SA">21733</additionalTradeItemIdentification>
        <additionalTradeItemIdentification
additionalTradeItemIdentificationTypeCode="ON">7369597</additionalTradeItemIdentification>
        <tradeItemDescription languageCode="NO">Article description</tradeItemDescription>
    </transactionalTradeItem>
</orderLineItem>
</order>
</ns0:orderMessage>

```