



Message Implementation Guideline

Despatch Order inbound XML - Axia

Model: DespatchAdvice-inbound Axia
Version: GS1 BMS 3.1
Variant: 3
Issue date: 2017-03-21
Author: Eva H Walldow

1 Structure	3
2 Guideline	5

Change Log DespatchAdvice-inbound Axia

Date	Variant	Comments
2015-09-18	2	<note languageCode="NO"> 450347 </note> added for Purchase Order number
2017-03-21	3	despatchAdvice/deliveryTypeCode = 220 for normal process
2017-03-21	3	despatchAdvice/deliveryTypeCode = 224 for express process

Structure

Occurrence	Element/Attribute
	despatchAdviceMessage
1 .. 1	xsd:sequence
1 .. 1	sh:StandardBusinessDocumentHeader
1 .. 1	xs:sequence
1 .. 1	HeaderVersion
1 .. unbounded	Sender
1 .. 1	xs:sequence
1 .. 1	Identifier
	<i>Authority</i>
1 .. unbounded	Receiver
1 .. 1	xs:sequence
1 .. 1	Identifier
	<i>Authority</i>
1 .. 1	DocumentIdentification
1 .. 1	xs:sequence
1 .. 1	Standard
1 .. 1	TypeVersion
1 .. 1	Instanceldentification
1 .. 1	Type
1 .. 1	CreationDateAndTime
1 .. 10000	despatchAdvice
1 .. 1	xsd:sequence
1 .. 1	creationDateTime
1 .. 1	documentStatusCode
1 .. 1	xsd:sequence
1 .. 1	despatchAdviceIdentification
1 .. 1	xs:sequence
1 .. 1	entityIdentification
0 .. 1	deliveryTypeCode
0 .. 1	note
required	<i>languageCode</i>
1 .. 1	receiver
1 .. 1	xs:sequence
0 .. 1	gln
1 .. 1	shipper
1 .. 1	xs:sequence
0 .. unbounded	additionalPartyIdentification
required	<i>additionalPartyIdentificationTypeCode</i>
1 .. 1	shipTo
1 .. 1	xs:sequence
0 .. unbounded	additionalPartyIdentification
required	<i>additionalPartyIdentificationTypeCode</i>
1 .. 1	despatchInformation
1 .. 1	xs:sequence
0 .. 1	estimatedDeliveryDateTime
0 .. unbounded	despatchAdviceLogisticUnit
1 .. 1	xs:sequence
0 .. 1	logisticUnitIdentification

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
1 .. 1	xsd:sequence
1 .. 1	sscc
1 .. 1	xsd:sequence
0 .. unbounded	despatchAdviceLineItem
1 .. 1	xsd:sequence
1 .. 1	lineItemNumber
1 .. 1	despatchedQuantity
	<i>measurementUnitCode</i>
0 .. 1	note
required	<i>languageCode</i>
1 .. 1	transactionalTradeltem
1 .. 1	xsd:sequence
1 .. 1	gtin
0 .. unbounded	additionalTradeltemIdentification
required	<i>additionalTradeltemIdentificationTypeCode</i>
1 .. 1	xsd:sequence
0 .. 1	productVariantIdentifier
0 .. unbounded	transactionalItemData
1 .. 1	xsd:sequence
0 .. 1	batchNumber
0 .. 1	bestBeforeDate
0 .. 1	productionDate

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Guideline

Element/Attribute	Annotation
despatchAdviceMessage	Type despatch_advice:DespatchAdviceMessageType
xsd:sequence	Occurrence 1 .. 1
sh:StandardBusinessDocumentHeader	Occurrence 1 .. 1 Type sh:StandardBusinessDocumentHeader
xsd:sequence	Occurrence 1 .. 1
HeaderVersion	Occurrence 1 .. 1 Type xsd:string Example 3.1
Sender	Occurrence 1 .. unbounded Type sh:Partner
xsd:sequence	Occurrence 1 .. 1
Identifier	Occurrence 1 .. 1 Type sh:PartnerIdentification Remark Client Id Example 12345
Receiver	Occurrence 1 .. unbounded Type sh:Partner
xsd:sequence	Occurrence 1 .. 1
Identifier	Occurrence 1 .. 1 Type sh:PartnerIdentification Remark GLN for receiver of the message Example 7393321400011
DocumentIdentification	Occurrence 1 .. 1 Type sh:DocumentIdentification
xsd:sequence	Occurrence 1 .. 1
Standard	Occurrence 1 .. 1 Type xsd:string Example GS1 BMS
TypeVersion	Occurrence 1 .. 1 Type xsd:string Example 3.1
InstanceIdentifier	Occurrence 1 .. 1 Type xsd:string Example GS1
Type	Occurrence 1 .. 1 Type xsd:string Example DespatchAdviceInbound
CreationDateAndTime	Occurrence 1 .. 1 Type xsd:dateTime Remark Message date/time Example 2014-09-24T10:15:25
despatchAdvice	Occurrence 1 .. 10000 Type despatch_advice:DespatchAdviceType
xsd:sequence	Occurrence 1 .. 1
creationDateTime	Occurrence 1 .. 1 Type xsd:dateTime Remark Document date/time Example 2014-09-25T09:50:00
documentStatusCode	Occurrence 1 .. 1 Type shared_common:DocumentStatusEnumerationType Example ORIGINAL
Applicable Codes	
ORIGINAL	
xsd:sequence	Occurrence 1 .. 1

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation				
despatchAdviceIdentification	<p>Occurrence 1 .. 1</p> <p>Type shared_common:EntityIdentificationType</p>				
xsd:sequence	<p>Occurrence 1 .. 1</p>				
entityIdentification	<p>Occurrence 1 .. 1</p> <p>Type restriction (xsd:string)</p> <p>Length 1 .. 80</p> <p>Remark Purchase order number or reference to the message</p> <p>Example 456789</p>				
deliveryTypeCode	<p>Occurrence 0 .. 1</p> <p>Type ecom_common:DeliveryTypeCodeType</p> <p>Length 1 .. 80</p> <p>Remark 220 to be used for a standard inbound process</p> <p>Remark 224 to be used for express inbound process</p> <p>Remark S to be used for Sampakk</p> <p>Example 220</p> <p>Applicable Codes</p> <table border="0"> <tr> <td>220</td> <td>Order</td> </tr> <tr> <td>224</td> <td>Rush order</td> </tr> </table>	220	Order	224	Rush order
220	Order				
224	Rush order				
note	<p>Occurrence 0 .. 1</p> <p>Type shared_common:Description500Type</p> <p>Length 1 .. 500</p> <p>Remark Element to be used for additional referens, as Purchase Order no.,which is searchable in Axia.</p> <p>Example 450347</p>				
<i>languageCode</i>	<p>Type restriction (xsd:string)</p> <p>Length 1 .. 80</p> <p>Use required</p> <p>Example NO</p>				
receiver	<p>Occurrence 1 .. 1</p> <p>Type ecom_common:TransactionalPartyType</p>				
xsd:sequence	<p>Occurrence 1 .. 1</p>				
gln	<p>Occurrence 0 .. 1</p> <p>Type shared_common:GLNType</p> <p>Pattern \d{13}</p> <p>Remark GLN for receiver (Warehouse)</p> <p>Example 7393321401018</p>				
shipper	<p>Occurrence 1 .. 1</p> <p>Type ecom_common:TransactionalPartyType</p>				
xsd:sequence	<p>Occurrence 1 .. 1</p>				
additionalPartyIdentification	<p>Occurrence 0 .. unbounded</p> <p>Type shared_common:AdditionalPartyIdentificationType</p> <p>Length 1 .. 80</p> <p>Remark Id for shipper (Supplier)</p> <p>Example 7890</p>				
<i>additionalPartyIdentificationTypeCode</i>	<p>Type restriction (xsd:string)</p> <p>Length 1 .. 80</p> <p>Use required</p> <p>Example 88</p> <p>Applicable Codes</p> <table border="0"> <tr> <td>88</td> <td>Assigned by the owner of operation</td> </tr> </table>	88	Assigned by the owner of operation		
88	Assigned by the owner of operation				
shipTo	<p>Occurrence 1 .. 1</p> <p>Type ecom_common:TransactionalPartyType</p> <p>Remark Only used for Bring Frigo Domestic traffic</p>				
xsd:sequence	<p>Occurrence 1 .. 1</p>				

Bold = Element, *Italic* = Attribute, Grey = Group



Element/Attribute	Annotation
additionalPartyIdentification	<p>Occurrence 0 .. unbounded Type shared_common:AdditionalPartyIdentificationType Length 1 .. 80 Remark Warehouse code for Bring Example BERGER</p> <p>Applicable Codes 4033 5500 BERGER BS07 BS17 BS19 BS24 NCD</p>
<i>additionalPartyIdentificationTypeCode</i>	<p>Type restriction (xsd:string) Length 1 .. 80 Use required Example 88</p> <p>Applicable Codes 87 Assigned by carrier 88 Assigned by the owner of operation</p>
despatchInformation	<p>Occurrence 1 .. 1 Type ecom_common:DespatchInformationType</p>
<i>xsd:sequence</i>	Occurrence 1 .. 1
estimatedDeliveryDateTime	<p>Occurrence 0 .. 1 Type xsd:dateTime Remark Delivery Date/Time Example 2014-10-15T15:00</p>
despatchAdviceLogisticUnit	<p>Occurrence 0 .. unbounded Type despatch_advice:DespatchAdviceLogisticUnitType</p>
<i>xsd:sequence</i>	Occurrence 1 .. 1
logisticUnitIdentification	<p>Occurrence 0 .. 1 Type shared_common:LogisticUnitIdentificationType</p>
<i>xsd:sequence</i>	Occurrence 1 .. 1
sscc	<p>Occurrence 1 .. 1 Type shared_common:SSCCType Pattern \d{18} Remark SSCC Example 373655645638436204</p>
<i>xsd:sequence</i>	Occurrence 1 .. 1
despatchAdviceLineItem	<p>Occurrence 0 .. unbounded Type despatch_advice:DespatchAdviceLineItemType</p>
<i>xsd:sequence</i>	Occurrence 1 .. 1
lineItemNumber	<p>Occurrence 1 .. 1 Type xsd:positiveInteger FractionDigits 0 Inclusive 1 .. Remark Order line number Example 1</p>
despatchedQuantity	<p>Occurrence 1 .. 1 Type shared_common:QuantityType Remark Despatch quantity Example 9</p>
<i>measurementUnitCode</i>	<p>Type restriction (xsd:string) Length 1 .. 80 Example PCE</p>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	Applicable Codes
	PCE pieces
note	<p>Occurrence 0 .. 1</p> <p>Type shared_common:Description500Type</p> <p>Length 1 .. 500</p> <p>Remark Refers to order line - to be returned in the confirmation of the order</p> <p>Example 12346-9082-01</p>
<i>languageCode</i>	<p>Type restriction (xsd:string)</p> <p>Length 1 .. 80</p> <p>Use required</p> <p>Example NO</p>
	Applicable Codes
	NO
transactionalTradeltem	<p>Occurrence 1 .. 1</p> <p>Type ecom_common:TransactionalTradeltemType</p>
xsd:sequence	Occurrence 1 .. 1
gtin	<p>Occurrence 1 .. 1</p> <p>Type shared_common:GTINType</p> <p>Pattern \d{14}</p> <p>Remark GTIN (GS1 article number) if not used fill in zeroes</p> <p>Example 000000000000</p>
additionalTradeltemIdentification	<p>Occurrence 0 .. unbounded</p> <p>Type shared_common:AdditionalTradeltemIdentificationType</p> <p>Length 1 .. 80</p> <p>Remark Supplier's aticle number</p> <p>Example 223344</p> <p>Remark Buyer's item number</p> <p>Example 65432</p>
<i>additionalTradeltemIdentificationTypeCode</i>	<p>Type restriction (xsd:string)</p> <p>Length 1 .. 80</p> <p>Use required</p> <p>Example SA</p> <p>Example IN</p>
	Applicable Codes
	IN Buyer's Item number
	SA Supplier's article number
xsd:sequence	Occurrence 1 .. 1
productVariantIdentifier	<p>Occurrence 0 .. 1</p> <p>Type restriction (xsd:string)</p> <p>Length 1 .. 80</p> <p>Description Only used by Bring Frigo</p> <p>Remark Goods charcteristics</p> <p>Example 1</p>
	Applicable Codes
	1 Frozen
	2 Chilled
	3 Dry
transactionalItemData	<p>Occurrence 0 .. unbounded</p> <p>Type ecom_common:TransactionalltemDataType</p>
xsd:sequence	Occurrence 1 .. 1
batchNumber	<p>Occurrence 0 .. 1</p> <p>Type restriction (xsd:string)</p> <p>Length 1 .. 80</p> <p>Remark Batch number</p> <p>Example 110621</p>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
<ul style="list-style-type: none"> — bestBeforeDate 	<p>Occurrence 0 .. 1 Type xsd:date Description <i>Only used by Bring Frigo</i> Remark Best before date Example 2015-01-01</p>
<ul style="list-style-type: none"> — productionDate 	<p>Occurrence 0 .. 1 Type xsd:date Description <i>Only used by Bring Frigo</i> Remark Production date Example 2014-09-30</p>

```

<?xml version="1.0" encoding="UTF-8" ?>
- <despatch_advice:despatchAdviceMessage
  xmlns:despatch_advice="urn:gs1:ecom:despatch_advice:xsd:3"
  xmlns:sh="http://www.unece.org/cefact/namespaces/StandardBusinessDocument
  Header">
- <sh:StandardBusinessDocumentHeader>
  <sh:HeaderVersion>3.1</sh:HeaderVersion>
- <sh:Sender>
  <sh:Identifier Authority="14">12345</sh:Identifier>
  </sh:Sender>
- <sh:Receiver>
  <sh:Identifier Authority="14">73933214000011</sh:Identifier>
  </sh:Receiver>
- <sh:DocumentIdentification>
  <sh:Standard>GS1 BMS</sh:Standard>
  <sh:TypeVersion>3.1</sh:TypeVersion>
  <sh:InstanceIdentifier>GS1</sh:InstanceIdentifier>
  <sh:Type>DespatchAdviceInbound</sh:Type>
  <sh:CreationDateAndTime>2014-09-24T10:15:25</sh:CreationDateAndTime>
  </sh:DocumentIdentification>
  </sh:StandardBusinessDocumentHeader>
- <despatchAdvice>
  <creationDateTime>2014-09-25T09:50:00</creationDateTime>
  <documentStatusCode>ORIGINAL</documentStatusCode>
- <despatchAdviceIdentification>
  <entityIdentification>456789</entityIdentification>
  </despatchAdviceIdentification>
  <deliveryTypeCode>220</deliveryTypeCode>
  <note languageCode="NO">450347</note>
- <receiver>
  <gln>7393321401018</gln>
  </receiver>
- <shipper>
  <additionalPartyIdentification
    additionalPartyIdentificationTypeCode="88">7890</additionalPartyIdentification>
  </shipper>
- <shipTo>
  <additionalPartyIdentification
    additionalPartyIdentificationTypeCode="88">BERGER</additionalPartyIdentification>
  </shipTo>
- <despatchInformation>
  <estimatedDeliveryDateTime>2014-10-15T15:00</estimatedDeliveryDateTime>
  </despatchInformation>
- <despatchAdviceLogisticUnit>
- <logisticUnitIdentification>
  <sscc>373655645638436204</sscc>
  </logisticUnitIdentification>
- <despatchAdviceLineItem>

```

Bold = Element, Italic = Attribute, Grey = Group

DespatchAdvice-inbound Axia; GS1 BMS 3.1; 3

Generated by GEFEG.FX

Issue date: 2017-03-21

Print date: 2017-03-21

Page: 10 / 11

```
<lineItemNumber>1</lineItemNumber>
<despatchedQuantity measurementUnitCode="PCE">9</despatchedQuantity>
<note languageCode="NO">12346-9082-01</note>
- <transactionalTradeItem>
  <gtin>0000000000000</gtin>
  <additionalTradeItemIdentification
    additionalTradeItemIdentificationTypeCode="SA">223344</additionalTradeItemIdentificati
    on>
  <productVariantIdentifier>1</productVariantIdentifier>
- <transactionalItemData>
  <batchNumber>110621</batchNumber>
  <bestBeforeDate>2015-01-01</bestBeforeDate>
  <productionDate>2014-09-30</productionDate>
  </transactionalItemData>
  </transactionalTradeItem>
  </despatchAdviceLineItem>
  </despatchAdviceLogisticUnit>
  </despatchAdvice>
  </despatch_advice:despatchAdviceMessage>
```