



Message Implementation Guideline

Despatch Advice Outbound XML

Model: DespatchAdvice-outbound
Version: GS1 BMB 3.1
Variant: 6
Issue date: 03.04.2019
Author: Vidar Thoresen

1 Structure	3
2 Guideline	6

Change log DespatchAdvice-outbound

Date	Variant	Comments
14.04.2019	6	Merged GS1 3.1 for Axia and Nyce systems

Structure

Occurrence	Element/Attribute
	despatchAdviceMessage
1 .. 1	xsd:sequence
1 .. 1	sh:StandardBusinessDocumentHeader
1 .. 1	xs:sequence
1 .. 1	HeaderVersion
1 .. unbounded	Sender
1 .. 1	xs:sequence
1 .. 1	Identifier
	<i>Authority</i>
1 .. unbounded	Receiver
1 .. 1	xs:sequence
1 .. 1	Identifier
1 .. 1	DocumentIdentification
1 .. 1	xs:sequence
1 .. 1	Standard
1 .. 1	TypeVersion
1 .. 1	InstanceIdentifier
1 .. 1	Type
1 .. 1	CreationDateAndTime
1 .. 10000	despatchAdvice
1 .. 1	xs:sequence
1 .. 1	creationDateTime
1 .. 1	documentStatusCode
1 .. 1	xs:sequence
1 .. 1	despatchAdviceIdentification
1 .. 1	xs:sequence
1 .. 1	entityIdentification
0 .. 1	deliveryTypeCode
0 .. 1	note
required	<i>languageCode</i>
1 .. 1	receiver
1 .. 1	xs:sequence
0 .. unbounded	additionalPartyIdentification
required	<i>additionalPartyIdentificationTypeCode</i>
1 .. 1	shipper
1 .. 1	xs:sequence
0 .. 1	gln
1 .. 1	shipTo
1 .. 1	xs:sequence
0 .. unbounded	additionalPartyIdentification
required	<i>additionalPartyIdentificationTypeCode</i>
0 .. 1	address
1 .. 1	xs:sequence
0 .. 1	city
0 .. 1	countryCode
0 .. 1	name
0 .. 1	postalCode
0 .. 1	streetAddressOne
	inventoryLocation

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
1 .. 1	<ul style="list-style-type: none"> xsd:sequence gln additionalPartyIdentification <i>additionalPartyIdentificationTypeCode</i>
1 .. 1	
0 .. 1	
1 .. 1	
required	
1 .. 1	despatchInformation
1 .. 1	<ul style="list-style-type: none"> xsd:sequence despatchDateTime estimatedDeliveryDateTime
0 .. 1	
0 .. 1	
0 .. 1	despatchAdviceTransportInformation
1 .. 1	<ul style="list-style-type: none"> xsd:sequence
0 .. 1	consignmentIdentification
1 .. 1	<ul style="list-style-type: none"> xsd:sequence
1 .. 1	ginc
0 .. unbounded	despatchAdviceLogisticUnit
1 .. 1	<ul style="list-style-type: none"> xsd:sequence
0 .. 1	logisticUnitIdentification
1 .. 1	<ul style="list-style-type: none"> xsd:sequence
1 .. 1	sscc
0 .. 1	logisticUnitMeasurement
1 .. 1	<ul style="list-style-type: none"> xsd:sequence
0 .. unbounded	unitMeasurement
1 .. 1	<ul style="list-style-type: none"> xsd:sequence measurementType measurementValue <i>measurementUnitCode</i>
1 .. 1	
1 .. 1	
required	
1 .. 1	<ul style="list-style-type: none"> xsd:sequence
0 .. unbounded	despatchAdviceLineItem
1 .. 1	<ul style="list-style-type: none"> xsd:sequence
1 .. 1	lineItemNumber
1 .. 1	despatchedQuantity
	<i>measurementUnitCode</i>
0 .. 1	note
required	<i>languageCode</i>
1 .. 1	transactionalTradeItem
1 .. 1	<ul style="list-style-type: none"> xsd:sequence
1 .. 1	gtin
0 .. unbounded	additionalTradeItemIdentification
required	<i>additionalTradeItemIdentificationTypeCode</i>
1 .. 1	<ul style="list-style-type: none"> xsd:sequence
0 .. unbounded	transactionalItemData
1 .. 1	<ul style="list-style-type: none"> xsd:sequence
0 .. 1	batchNumber
0 .. 1	bestBeforeDate
0 .. 1	lotNumber
0 .. unbounded	serialNumber
0 .. unbounded	transactionalItemWeight
1 .. 1	<ul style="list-style-type: none"> xsd:sequence measurementType measurementValue <i>measurementUnitCode</i>
1 .. 1	
1 .. 1	
required	

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
0 .. 1	customerReference
1 .. 1	xsd:sequence
1 .. 1	entityIdentification

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Guideline

Element/Attribute	Annotation
despatchAdviceMessage	Type despatch_advice:DespatchAdviceMessageType
xsd:sequence	Occurrence 1 .. 1
sh:StandardBusinessDocumentHeader	Occurrence 1 .. 1 Type sh:StandardBusinessDocumentHeader
xsd:sequence	Occurrence 1 .. 1
HeaderVersion	Occurrence 1 .. 1 Type xsd:string Example 3.1
Sender	Occurrence 1 .. unbounded Type sh:Partner
xsd:sequence	Occurrence 1 .. 1
Identifier	Occurrence 1 .. 1 Type sh:PartnerIdentification Remark GLN (GS1 location code) for sender of the message Example 7080000950171
<i>Authority</i>	Type xsd:string Example 14
Receiver	Occurrence 1 .. unbounded Type sh:Partner
xsd:sequence	Occurrence 1 .. 1
Identifier	Occurrence 1 .. 1 Type sh:PartnerIdentification Remark Client id Example 123456
DocumentIdentification	Occurrence 1 .. 1 Type sh:DocumentIdentification
xsd:sequence	Occurrence 1 .. 1
Standard	Occurrence 1 .. 1 Type xsd:string Example GS1 BMS
TypeVersion	Occurrence 1 .. 1 Type xsd:string Example 3.1
InstanceIdentifier	Occurrence 1 .. 1 Type xsd:string Example GS1
Type	Occurrence 1 .. 1 Type xsd:string Example DespatchAdviceOutbound
CreationDateAndTime	Occurrence 1 .. 1 Type xsd:dateTime Remark Message date/time Example 2014-09-10T12:00:00
despatchAdvice	Occurrence 1 .. 10000 Type despatch_advice:DespatchAdviceType
xsd:sequence	Occurrence 1 .. 1
creationDateTime	Occurrence 1 .. 1 Type xsd:dateTime Remark Document date/time Example 2014-09-10T11:00:00

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
documentStatusCode	Occurrence 1 .. 1 Type shared_common:DocumentStatusEnumerationType Example ORIGINAL Applicable Codes ORIGINAL
xsd:sequence	Occurrence 1 .. 1
despatchAdviceIdentification	Occurrence 1 .. 1 Type shared_common:EntityIdentificationType
xsd:sequence	Occurrence 1 .. 1
entityIdentification	Occurrence 1 .. 1 Type restriction (xsd:string) Length 1 .. 80 Remark Order number received in the Customer Order 'orderIdentification' Example 125987
deliveryTypeCode	Occurrence 0 .. 1 Type ecom_common:DeliveryTypeCodeType Length 1 .. 80 Remark Status code from Axia Example O4 Applicable Codes 99 Canceled O1 EDI / API data received O2 Order allocated O3 Order picked O4 Order sent
note	Occurrence 0 .. 1 Type shared_common:Description500Type Length 1 .. 500 Remark Additional reference received in Customer Order 'note' Example 69581A
<i>languageCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Remark Element required Example SE
receiver	Occurrence 1 .. 1 Type ecom_common:TransactionalPartyType
xsd:sequence	Occurrence 1 .. 1
additionalPartyIdentification	Occurrence 0 .. unbounded Type shared_common:AdditionalPartyIdentificationType Length 1 .. 80 Remark Client Id Example 123456
<i>additionalPartyIdentificationTypeCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example 88 Applicable Codes 88 Assigned by the owner of operation
shipper	Occurrence 1 .. 1 Type ecom_common:TransactionalPartyType
xsd:sequence	Occurrence 1 .. 1

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation
gln	Occurrence 0 .. 1 Type shared_common:GLNType Pattern \d{13} Description Only used by Bring Frigo Remark GLN (GS1 location code) for shipper (consignor) Example 73933217401018
shipTo	Occurrence 1 .. 1 Type ecom_common:TransactionalPartyType
xsd:sequence	Occurrence 1 .. 1
additionalPartyIdentification	Occurrence 0 .. unbounded Type shared_common:AdditionalPartyIdentificationType Length 1 .. 80 Remark Customer id for delivery party Example 50296
<i>additionalPartyIdentificationTypeCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example 88 Applicable Codes 88 Assigned by the owner of operation
address	Occurrence 0 .. 1 Type shared_common:AddressType
xsd:sequence	Occurrence 1 .. 1
city	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 200 Remark ShipTo cityname Example OSLO
countryCode	Occurrence 0 .. 1 Type shared_common:CountryCodeType Length 1 .. 80 Remark Use ISO 3166 Alpha Example NO
name	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 200 Remark ShipTo name Example ICA Kvantum
postalCode	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 80 Remark ShipTo postal code Example 1000
streetAddressOne	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 200 Remark ShipTo Street address Example Lagervejen 14
inventoryLocation	Occurrence 1 .. 1 Type ecom_common:TransactionalPartyType
xsd:sequence	Occurrence 1 .. 1
gln	Occurrence 0 .. 1 Type shared_common:GLNType Pattern \d{13} Remark GLN for warehouse location Example 7393321401018

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation
additionalPartyIdentification	Occurrence 1 .. 1 Type shared_common:AdditionalPartyIdentificationType Length 1 .. 80 Remark Warehouse location Example BERGER
	Applicable Codes
	4033 Stavanger (Norway) 5500 Haugesund (Norway) AES Ålesund (Norway) BERGER Berger/Skedsmokorset (Norway) BS02 Kongshavn (Norway) BS07 Trollåsen (Norway) BS17 Bergen (Norway) BS26 Trondheim (Norway) BS34 Tromsø (Norway) FI01 (Finland) JKPG01 Jönköping (Sweden) NCD Lierstrand (Norway)
despatchInformation	Occurrence 1 .. 1 Type ecom_common:DespatchInformationType
xsd:sequence	
despatchDateTime	Occurrence 1 .. 1 Type xsd:dateTime Remark Despatch date/time from warehouse Example 2014-10-09T10:12:00
estimatedDeliveryDateTime	Occurrence 0 .. 1 Type xsd:dateTime Remark Estimated delivery Date Example 2014-10-11T00:00:00
despatchAdviceTransportInformation	Occurrence 0 .. 1 Type despatch_advice:DespatchAdviceTransportInformationType
xsd:sequence	
consignmentIdentification	Occurrence 0 .. 1 Type shared_common:ConsignmentIdentificationType
xsd:sequence	
ginc	Occurrence 1 .. 1 Type shared_common:GINCType Pattern [-!%&'()*+,-/0-9;=<=>?A-Z_a-z]{4,30} Remark GINC (Global Shipment Identification Number) Remark As this is a required element fill in '73500538500000019' if GINC not is in use Example 73500538500000019
despatchAdviceLogisticUnit	Occurrence 0 .. unbounded Type despatch_advice:DespatchAdviceLogisticUnitType
xsd:sequence	
logisticUnitIdentification	Occurrence 0 .. 1 Type shared_common:LogisticUnitIdentificationType
xsd:sequence	
sscc	Occurrence 1 .. 1 Type shared_common:SSCCType Pattern \d{18} Remark SSCC (Serial shipping container code) Example 373323991248161986
logisticUnitMeasurement	Occurrence 0 .. 1 Type ecom_common:LogisticUnitMeasurementType

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation
unitMeasurement	<p>Occurrence 1 .. 1</p> <p>Occurrence 0 .. unbounded</p> <p>Type ecom_common:UnitMeasurementType</p>
measurementType	<p>Occurrence 1 .. 1</p> <p>Occurrence 1 .. 1</p> <p>Type ecom_common:MeasurementTypeCodeType</p> <p>Length 1 .. 80</p> <p>Example AAD</p> <p>Applicable Codes</p> <p>AAD Total Gross Weight</p>
measurementValue	<p>Occurrence 1 .. 1</p> <p>Type shared_common:MeasurementType</p> <p>Remark Total Gross Weight</p> <p>Example 825</p>
<i>measurementUnitCode</i>	<p>Type restriction (xsd:string)</p> <p>Length 1 .. 80</p> <p>Use required</p> <p>Example KGM</p> <p>Applicable Codes</p> <p>KGM kilogram</p>
despatchAdviceLineItem	<p>Occurrence 1 .. 1</p> <p>Occurrence 0 .. unbounded</p> <p>Type despatch_advice:DespatchAdviceLineItemType</p>
lineItemNumber	<p>Occurrence 1 .. 1</p> <p>Occurrence 1 .. 1</p> <p>Type xsd:positiveInteger</p> <p>FractionDigits 0</p> <p>Inclusive 1 ..</p> <p>Remark Line item number</p> <p>Example 1</p>
despatchedQuantity	<p>Occurrence 1 .. 1</p> <p>Type shared_common:QuantityType</p> <p>Remark Number of packages despatched</p> <p>Example 50</p>
<i>measurementUnitCode</i>	<p>Type restriction (xsd:string)</p> <p>Length 1 .. 80</p> <p>Example PCE</p> <p>Applicable Codes</p> <p>PCE pieces</p>
note	<p>Occurrence 0 .. 1</p> <p>Type shared_common:Description500Type</p> <p>Length 1 .. 500</p> <p>Remark Note sent i the CustomerOrder will be returned</p> <p>Example 12-234-90A</p>
<i>languageCode</i>	<p>Type restriction (xsd:string)</p> <p>Length 1 .. 80</p> <p>Use required</p> <p>Example NO</p> <p>Applicable Codes</p> <p>NO</p>
transactionalTradeItem	<p>Occurrence 1 .. 1</p> <p>Type ecom_common:TransactionalTradeItemType</p>
gtin	<p>Occurrence 1 .. 1</p> <p>Occurrence 1 .. 1</p> <p>Type shared_common:GTINType</p> <p>Pattern \d{14}</p>

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
	Remark GTIN 13 (GS1 article number) if not used fillin zeros Example 0000000000000
additionalTradeItemIdentification	Occurrence 0 .. unbounded Type shared_common:AdditionalTradeItemIdentificationType Length 1 .. 80 Remark Supplier's article number Example 123456
<i>additionalTradeItemIdentificationTypeCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example IN Applicable Codes IN Buyer's Item number SA Supplier's article number ZGR Grade
xsd:sequence	Occurrence 1 .. 1
transactionalItemData	Occurrence 0 .. unbounded Type ecom_common:TransactionalItemDataType
xsd:sequence	Occurrence 1 .. 1
batchNumber	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 80 Remark Batch number Example 2514780
bestBeforeDate	Occurrence 0 .. 1 Type xsd:date Remark Best before date (CCYYMMDD) Example 150101
lotNumber	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 80 Remark IMEI number Example 352052063095991
serialNumber	Occurrence 0 .. unbounded Type restriction (xsd:string) Length 1 .. 20 Remark Serial number Example DX3N4582GH4
transactionalItemWeight	Occurrence 0 .. unbounded Type ecom_common:UnitMeasurementType
xsd:sequence	Occurrence 1 .. 1
measurementType	Occurrence 1 .. 1 Type ecom_common:MeasurementTypeCodeType Length 1 .. 80 Example AAC Applicable Codes AAC Total net weight
measurementValue	Occurrence 1 .. 1 Type shared_common:MeasurementType Remark Total net weight Example 750
<i>measurementUnitCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example KGM

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	Applicable Codes
	KGM kilogram
customerReference	Occurrence 0 .. 1
	Type shared_common:DocumentReferenceType
<i>xsd:sequence</i>	Occurrence 1 .. 1
entityIdentification	Occurrence 1 .. 1
	Type restriction (xsd:string)
	Length 1 .. 80
	Remark Customer Reference
	Example 69581A

```

<?xml version="1.0" encoding="utf-8"?>
<ns0:despatchAdviceMessage xmlns:ns0="urn:gs1:ecom:despatch_advice:xsd:3">
  <sh:StandardBusinessDocumentHeader
xmlns:sh="http://www.unece.org/cefact/namespaces/StandardBusinessDocumentHeader">
    <sh:HeaderVersion>3.1</sh:HeaderVersion>
    <sh:Sender>
      <sh:Identifier Authority="14">7080000950171</sh:Identifier>
    </sh:Sender>
    <sh:Receiver>
      <sh:Identifier Authority="30">999999</sh:Identifier>
    </sh:Receiver>
    <sh:DocumentIdentification>
      <sh:Standard>GS1 BMS</sh:Standard>
      <sh:TypeVersion>3.1</sh:TypeVersion>
      <sh:InstanceIdentifier>GS1</sh:InstanceIdentifier>
      <sh:Type>DespatchAdviceOutbound</sh:Type>
      <sh:CreationDateAndTime>2019-04-15T22:01:35</sh:CreationDateAndTime>
    </sh:DocumentIdentification>
  </sh:StandardBusinessDocumentHeader>
  <despatchAdvice>
    <creationDateTime>2019-04-13T17:00:18</creationDateTime>
    <creationDateTime>2019-04-13T17:00:18</creationDateTime>
    <documentStatusCode>ORIGINAL</documentStatusCode>
    <despatchAdviceIdentification>
      <entityIdentification>222333222</entityIdentification>
      <deliveryTypeCode>04</deliveryTypeCode>
      <note>1226543</note>
    </despatchAdviceIdentification>
    <shipTo>
      <address>
        <name>Customer name</name>
        <postalCode>1088</postalCode>
        <city>OSLO</city>
        <countrycode>NO</countrycode>
        <streetAddressOne>Customer street</streetAddressOne>
      </address>
      <contact />
    </shipTo>
    <inventoryLocation>
      <additionalPartyIdentification>NCD</additionalPartyIdentification>
    </inventoryLocation>
    <despatchInformation>
      <despatchDateTime>2019-04-13T00:00:00</despatchDateTime>
    </despatchInformation>
    <despatchAdviceTransportInformation>
      <consignmentIdentification>
        <ginc>7080000950171</ginc>
      </consignmentIdentification>
    </despatchAdviceTransportInformation>
    <despatchAdviceLogisticUnit>
      <despatchAdviceLineItem>
        <lineItemNumber>10</lineItemNumber>
        <transactionalTradeItem>
          <additionalTradeItemIdentification
additionalTradeItemIdentificationTypeCode="IN">11111111</additionalTradeItemIdentification>

```

Bold = Element, Italic = Attribute, Grey = Group

```

description</tradeltemDescription>
    <tradeltemDescription>Article one
    <transactionalItemData>
        <batchNumber>M11111</batchNumber>
        <tradeltemQuantity>
measurementUnitCode="PCE">1.0</tradeltemQuantity>
        </transactionalItemData>
    </transactionalTradeltem>
    <despatchedQuantity>
measurementUnitCode="PCE">1.0</despatchedQuantity>
    </despatchAdviceLineItem>
</despatchAdviceLogisticUnit>
<despatchAdviceLogisticUnit>
    <despatchAdviceLineItem>
        <lineItemNumber>20</lineItemNumber>
        <transactionalTradeltem>
            <additionalTradeltemIdentification
additionalTradeltemIdentificationTypeCode="IN">22222222</additionalTradeltemIdentification>
            <tradeltemDescription>Article two
description</tradeltemDescription>
            <transactionalItemData>
                <batchNumber>M22222</batchNumber>
                <tradeltemQuantity>
measurementUnitCode="PCE">1.0</tradeltemQuantity>
                </transactionalItemData>
            </transactionalTradeltem>
            <despatchedQuantity>
measurementUnitCode="PCE">1.0</despatchedQuantity>
            </despatchAdviceLineItem>
        </despatchAdviceLogisticUnit>
    </despatchAdvice>
</ns0:despatchAdviceMessage>

```