



Message Implementation Guideline

## InventoryReport XML

Model: InventoryReport  
Version: GS1 BMB 3.1  
Variant: 3  
Issue date: 03.04.2019  
Author: Vidar Thoresen

1 Structure .....	3
2 Guideline .....	5

---

# Change log InventoryReport

Date	Variant	Comments
14.04.2019	3	Merged GS1 3.1 for Axia and Nyce systems

## Structure

Occurrence	Element/Attribute
	<b>inventoryReportMessage</b>
1 .. 1	xsd:sequence
1 .. 1	<b>sh:StandardBusinessDocumentHeader</b>
1 .. 1	xs:sequence
1 .. 1	<b>HeaderVersion</b>
1 .. unbounded	<b>Sender</b>
1 .. 1	xs:sequence
1 .. 1	<b>Identifier</b>
	<i>Authority</i>
1 .. unbounded	<b>Receiver</b>
1 .. 1	xs:sequence
1 .. 1	<b>Identifier</b>
	<i>Authority</i>
1 .. 1	<b>DocumentIdentification</b>
1 .. 1	xs:sequence
1 .. 1	<b>Standard</b>
1 .. 1	<b>TypeVersion</b>
1 .. 1	<b>InstanceIdentifier</b>
1 .. 1	<b>Type</b>
1 .. 1	<b>CreationDateAndTime</b>
1 .. 10000	<b>inventoryReport</b>
1 .. 1	xsd:sequence
1 .. 1	<b>creationDateTime</b>
1 .. 1	<b>documentStatusCode</b>
1 .. 1	xsd:sequence
1 .. 1	<b>inventoryReportIdentification</b>
1 .. 1	xs:sequence
1 .. 1	<b>entityIdentification</b>
1 .. 1	<b>inventoryReportTypeCode</b>
1 .. 1	<b>structureTypeCode</b>
1 .. 1	<b>inventoryReportToParty</b>
1 .. 1	xs:sequence
0 .. unbounded required	<b>additionalPartyIdentification</b>
	<i>additionalPartyIdentificationTypeCode</i>
1 .. 1	<b>inventoryReportingParty</b>
1 .. 1	xs:sequence
0 .. 1	<b>gln</b>
1 .. 1	<b>reportingPeriod</b>
1 .. 1	xs:sequence
0 .. 1	<b>endDate</b>
1 .. unbounded	<b>inventoryItemLocationInformation</b>
1 .. 1	xs:sequence
1 .. 1	<b>inventoryLocation</b>
1 .. 1	xs:sequence
1 .. unbounded required	<b>additionalPartyIdentification</b>
	<i>additionalPartyIdentificationTypeCode</i>
1 .. 1	<b>transactionalTradeltem</b>
1 .. 1	xs:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
1 .. 1	<b>gtin</b>
0 .. unbounded required	<b>additionalTradeltemIdentification</b>
1 .. 1	<i>additionalTradeltemIdentificationTypeCode</i>
0 .. 1	xsd:sequence
0 .. 1	<b>tradeltemQuantity</b>
0 .. 1	<i>measurementUnitCode</i>
0 .. 1 required	<b>tradeltemDescription</b>
	<i>languageCode</i>
<b>0 .. unbounded</b>	<b>transactionalItemData</b>
1 .. 1	xsd:sequence
0 .. 1	<b>batchNumber</b>
0 .. 1	<b>bestBeforeDate</b>
0 .. unbounded	<b>serialNumber</b>
<b>0 .. unbounded</b>	<b>inventoryStatusLineItem</b>
1 .. 1	xsd:sequence
1 .. 1	<b>lineItemNumber</b>
<b>1 .. unbounded</b>	<b>inventoryStatusQuantitySpecification</b>
1 .. 1	xsd:sequence
1 .. 1	<b>inventoryStatusType</b>
1 .. 1	<b>quantityOfUnits</b>

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

## Guideline

Element/Attribute	Annotation
<b>inventoryReportMessage</b>	Type inventory_report:InventoryReportMessageType
xsd:sequence	Occurrence 1 .. 1
<b>sh:StandardBusinessDocumentHeader</b>	Occurrence 1 .. 1 Type sh:StandardBusinessDocumentHeader
xsd:sequence	Occurrence 1 .. 1
<b>HeaderVersion</b>	Occurrence 1 .. 1 Type xsd:string Example 3.1
<b>Sender</b>	Occurrence 1 .. unbounded Type sh:Partner
xsd:sequence	Occurrence 1 .. 1
<b>Identifier</b>	Occurrence 1 .. 1 Type sh:PartnerIdentification Remark <b>GLN for sender of the message</b> Example 7080000950171
<i>Authority</i>	Type xsd:string Example 14
<b>Receiver</b>	Occurrence 1 .. unbounded Type sh:Partner
xsd:sequence	Occurrence 1 .. 1
<b>Identifier</b>	Occurrence 1 .. 1 Type sh:PartnerIdentification Remark <b>Client Id</b> Example 12345
<i>Authority</i>	Type xsd:string Example ZZ
<b>Applicable Codes</b>	
14	EAN International
<b>Applicable Codes</b>	
ZZ	Mutually defined
<b>DocumentIdentification</b>	Occurrence 1 .. 1 Type sh:DocumentIdentification
xsd:sequence	Occurrence 1 .. 1
<b>Standard</b>	Occurrence 1 .. 1 Type xsd:string Example <b>GS1 BMS</b>
<b>TypeVersion</b>	Occurrence 1 .. 1 Type xsd:string Example 3.1
<b>InstanceIdentifier</b>	Occurrence 1 .. 1 Type xsd:string Example <b>GS1</b>
<b>Type</b>	Occurrence 1 .. 1 Type xsd:string Example <b>InventoryReport</b>
<b>CreationDateAndTime</b>	Occurrence 1 .. 1 Type xsd:dateTime Remark <b>Creation date/time for the message</b> Remark <b>2014-10-08T10:00:00</b>
<b>inventoryReport</b>	Occurrence 1 .. 10000 Type inventory_report:InventoryReportType
xsd:sequence	Occurrence 1 .. 1

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation
<b>creationDateTime</b>	Occurrence 1 .. 1 Type xsd:dateTime Remark <b>Creation date/tims for the document</b> Example <b>2014-10-08T10:00:00</b>
<b>documentStatusCode</b>	Occurrence 1 .. 1 Type shared_common:DocumentStatusEnumerationType Example <b>ORIGINAL</b> <b>Applicable Codes</b> <b>ORIGINAL</b>
xsd:sequence	Occurrence 1 .. 1
<b>inventoryReportIdentification</b>	Occurrence 1 .. 1 Type shared_common:EntityIdentificationType
xsd:sequence	Occurrence 1 .. 1
<b>entityIdentification</b>	Occurrence 1 .. 1 Type restriction (xsd:string) Length 1 .. 80 Remark <b>Document/message number</b> Example <b>4567819</b>
<b>inventoryReportTypeCode</b>	Occurrence 1 .. 1 Type inventory_report:InventoryReportTypeEnumerationType Example <b>INVENTORY_STATUS</b> <b>Applicable Codes</b> <b>INVENTORY_STATUS</b>
<b>structureTypeCode</b>	Occurrence 1 .. 1 Type ecom_common:StructureTypeCodeType Length 1 .. 80 Remark <b>Required</b> Example <b>1</b>
<b>inventoryReportToParty</b>	Occurrence 1 .. 1 Type ecom_common:TransactionalPartyType
xsd:sequence	Occurrence 1 .. 1
<b>additionalPartyIdentification</b>	Occurrence 0 .. unbounded Type shared_common:AdditionalPartyIdentificationType Length 1 .. 80 Remark <b>Client Id</b> Example <b>12345</b>
<i>additionalPartyIdentificationTypeCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required Example <b>88</b> <b>Applicable Codes</b> <b>88</b> Assigned by the owner of operation
<b>inventoryReportingParty</b>	Occurrence 1 .. 1 Type ecom_common:TransactionalPartyType
xsd:sequence	Occurrence 1 .. 1
<b>gln</b>	Occurrence 0 .. 1 Type shared_common:GLNType Pattern \d{13} Remark <b>GLN for reporting Party</b> Example <b>7080003388100</b>
<b>reportingPeriod</b>	Occurrence 1 .. 1 Type shared_common:DateTimeRangeType
xsd:sequence	Occurrence 1 .. 1
<b>endDate</b>	Occurrence 0 .. 1 Type xsd:date Remark <b>Activity report date</b>

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
<b>inventoryItemLocationInformation</b>	<b>Example</b> 2014-10-08 <b>Occurrence</b> 1 .. unbounded <b>Type</b> inventory_report:InventoryItemLocationInformationType
xsd:sequence	
<b>inventoryLocation</b>	<b>Occurrence</b> 1 .. 1 <b>Type</b> ecom_common:TransactionalPartyType
xsd:sequence	
<b>additionalPartyIdentification</b>	<b>Occurrence</b> 1 .. unbounded <b>Type</b> shared_common:AdditionalPartyIdentificationType <b>Length</b> 1 .. 80 <b>Remark</b> <b>Internal Warehouse code</b> <b>Example</b> <b>BERGER</b>
	<b>Applicable Codes</b>
	<b>4033</b> Stavanger (Norway)
	<b>5500</b> Haugesund (Norway)
	<b>AES</b> Ålesund (Norway)
	<b>BERGER</b> Berger/Skedsмокorset (Norway)
	<b>BS02</b> Kongshavn (Norway)
	<b>BS07</b> Trollåsen (Norway)
	<b>BS17</b> Bergen (Norway)
	<b>BS26</b> Trondheim (Norway)
	<b>BS34</b> Tromsø (Norway)
	<b>FI01</b> Finland
	<b>JKPG01</b> Jönköping (Sweden)
	<b>NCD</b> Lierstrand (Norway)
<i>additionalPartyIdentificationTypeCode</i>	<b>Type</b> restriction (xsd:string) <b>Length</b> 1 .. 80 <b>Use</b> required <b>Example</b> <b>88</b>
	<b>Applicable Codes</b>
	<b>88</b> Assigned by the owner of operation
<b>transactionalTradeltem</b>	<b>Occurrence</b> 1 .. 1 <b>Type</b> ecom_common:TransactionalTradeltemType
xsd:sequence	
<b>gtin</b>	<b>Occurrence</b> 1 .. 1 <b>Type</b> shared_common:GTINType <b>Pattern</b> \d{14} <b>Remark</b> <b>GTIN - if used otherwise zeros will be sent</b> <b>Example</b> <b>0000000000000</b>
<b>additionalTradeltemIdentification</b>	<b>Occurrence</b> 0 .. unbounded <b>Type</b> shared_common:AdditionalTradeltemIdentificationType <b>Length</b> 1 .. 80 <b>Remark</b> <b>Buyer's article number</b> <b>Example</b> <b>554488</b>
<i>additionalTradeltemIdentificationTypeCode</i>	<b>Type</b> restriction (xsd:string) <b>Length</b> 1 .. 80 <b>Use</b> required <b>Example</b> <b>IN</b>
	<b>Applicable Codes</b>
	<b>IN</b> Buyer's Item number
	<b>SA</b> Supplier's article number
	<b>ZGR</b> Grade
	<b>ZST</b> Status
xsd:sequence	
<b>tradeltemQuantity</b>	<b>Occurrence</b> 1 .. 1 <b>Type</b> shared_common:QuantityType <b>Remark</b> <b>Quantity in stock</b>

**Bold** = Element, *Italic* = Attribute, **Grey** = Group

Element/Attribute	Annotation
	<b>Example</b> 22
<i>measurementUnitCode</i>	Type restriction (xsd:string) Length 1 .. 80 <b>Example</b> PCE
	<b>Applicable Codes</b>
	PCE pieces
<b>tradelItemDescription</b>	Occurrence 0 .. 1 Type shared_common:Description200Type Length 1 .. 200
<i>languageCode</i>	Type restriction (xsd:string) Length 1 .. 80 Use required
	<b>Applicable Codes</b>
	FI FINLAND NO NORWAY SE SWEDEN
<b>transactionalItemData</b>	Occurrence 0 .. unbounded Type ecom_common:TransactionalItemType
xsd:sequence	Occurrence 1 .. 1
<b>batchNumber</b>	Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 80 <b>Remark</b> Batch number <b>Example</b> 123907
<b>bestBeforeDate</b>	Occurrence 0 .. 1 Type xsd:date <b>Remark</b> Best before date <b>Example</b> 20150101
<b>serialNumber</b>	Occurrence 0 .. unbounded Type restriction (xsd:string) Length 1 .. 20 <b>Remark</b> Serial number <b>Example</b> 2345678
<b>inventoryStatusLineItem</b>	Occurrence 0 .. unbounded Type inventory_report:InventoryStatusLineItemType
xsd:sequence	Occurrence 1 .. 1
<b>lineItemNumber</b>	Occurrence 1 .. 1 Type xsd:positiveInteger FractionDigits 0 Inclusive 1 .. <b>Example</b> 1
<b>inventoryStatusQuantitySpecification</b>	Occurrence 1 .. unbounded Type ecom_common:InventoryStatusQuantitySpecificationType
xsd:sequence	Occurrence 1 .. 1
<b>inventoryStatusType</b>	Occurrence 1 .. 1 Type ecom_common:InventoryStatusCodeType Length 1 .. 80 <b>Remark</b> Status <b>Example</b> AVAILABLE_FOR_SALE
	<b>Applicable Codes</b>
	AVAILABLE_FOR_SALE BLOCKED QUARANTINED
<b>quantityOfUnits</b>	Occurrence 1 .. 1 Type shared_common:QuantityType <b>Remark</b> Quantity in stock

**Bold** = Element, *Italic* = Attribute, **Grey** = Group





Element/Attribute	Annotation
-------------------	------------

Example 22

```

<?xml version="1.0" encoding="Windows-1252"?>
<ns0:inventoryReportMessage xmlns:ns0="urn:gs1:ecom:inventory_report:xsd:3">
  <sh:StandardBusinessDocumentHeader
xmlns:sh="http://www.unece.org/cefact/namespaces/StandardBusinessDocumentHeader">
    <sh:HeaderVersion>3.1</sh:HeaderVersion>
    <sh:Sender>
      <sh:Identifier Authority="14">7080000950171</sh:Identifier>
    </sh:Sender>
    <sh:Receiver>
      <sh:Identifier Authority="ZZ">999999</sh:Identifier>
    </sh:Receiver>
    <sh:DocumentIdentification>
      <sh:Standard>GS1 BMS</sh:Standard>
      <sh:TypeVersion>3.1</sh:TypeVersion>
      <sh:InstanceIdentifier>GS1</sh:InstanceIdentifier>
      <sh:Type>InventoryReport</sh:Type>
      <sh:CreationDateAndTime>2019-04-10T10:49:07</sh:CreationDateAndTime>
    </sh:DocumentIdentification>
  </sh:StandardBusinessDocumentHeader>
  <inventoryReport>
    <creationDateTime>2019-04-10T05:30:00</creationDateTime>
    <documentStatusCode>ORIGINAL</documentStatusCode>
    <inventoryReportTypeCode>INVENTORY_STATUS</inventoryReportTypeCode>
    <structureTypeCode>ITEM_BY_LOCATION</structureTypeCode>
    <inventoryReportToParty>
      <additionalPartyIdentification
additionalPartyIdentificationTypeCode="88">999999</additionalPartyIdentification>
    </inventoryReportToParty>
    <inventoryReportingParty>
      <additionalPartyIdentification
additionalPartyIdentificationTypeCode="88">BERGER</additionalPartyIdentification>
    </inventoryReportingParty>
    <reportingPeriod>
      <endDate>2019-04-10</endDate>
    </reportingPeriod>
    <inventoryItemLocationInformation>
      <inventoryLocation>
        <additionalPartyIdentification
additionalPartyIdentificationTypeCode="88">BERGER</additionalPartyIdentification>
      </inventoryLocation>
      <transactionalTradeItem>
        <gtin>00000000000000</gtin>
        <additionalTradeItemIdentification
additionalTradeItemIdentificationTypeCode="BUYER_ASSIGNED">111111111111</additionalTradeItemIdentific
ation>
          <tradeItemQuantity measurementUnitCode="PCE">1</tradeItemQuantity>
        </transactionalTradeItem>
      <inventoryStatusLineItem>
        <lineItemNumber>1</lineItemNumber>
        <inventoryStatusQuantitySpecification>
          <inventoryStatusType>AVAILABLE_FOR_SALE</inventoryStatusType>
          <quantityOfUnits
measurementUnitCode="STK">1</quantityOfUnits>
        </inventoryStatusQuantitySpecification>
      </inventoryStatusLineItem>
    </inventoryItemLocationInformation>
  </inventoryReport>
</ns0:inventoryReportMessage>

```

Bold = Element, *Italic* = Attribute, Grey = Group

```

        </inventoryStatusLineItem>
    </inventoryItemLocationInformation>
<inventoryItemLocationInformation>
    <inventoryLocation>
        <additionalPartyIdentification
additionalPartyIdentificationTypeCode="88">BERGER</additionalPartyIdentification>
        </inventoryLocation>
    <transactionalTradelItem>
        <gtin>00000000000000</gtin>
        <additionalTradelItemIdentification
additionalTradelItemIdentificationTypeCode="BUYER_ASSIGNED">222222222222</additionalTradelItemIdentific
ation>
            <tradelItemQuantity
measurementUnitCode="PCE">12</tradelItemQuantity>
        </transactionalTradelItem>
    </inventoryStatusLineItem>
        <lineItemNumber>2</lineItemNumber>
    <inventoryStatusQuantitySpecification>

    <inventoryStatusType>AVAILABLE_FOR_SALE</inventoryStatusType>
        <quantityOfUnits
measurementUnitCode="STK">12</quantityOfUnits>
    </inventoryStatusQuantitySpecification>
    </inventoryStatusLineItem>
</inventoryItemLocationInformation>
<inventoryItemLocationInformation>
    <inventoryLocation>
        <additionalPartyIdentification
additionalPartyIdentificationTypeCode="88">BERGER</additionalPartyIdentification>
        </inventoryLocation>
    <transactionalTradelItem>
        <gtin>00000000000000</gtin>
        <additionalTradelItemIdentification
additionalTradelItemIdentificationTypeCode="BUYER_ASSIGNED">333333333333</additionalTradelItemIdentific
ation>
            <tradelItemQuantity measurementUnitCode="PCE">5</tradelItemQuantity>
        </transactionalTradelItem>
    </inventoryStatusLineItem>
        <lineItemNumber>3</lineItemNumber>
    <inventoryStatusQuantitySpecification>

    <inventoryStatusType>AVAILABLE_FOR_SALE</inventoryStatusType>
        <quantityOfUnits
measurementUnitCode="STK">5</quantityOfUnits>
    </inventoryStatusQuantitySpecification>
    </inventoryStatusLineItem>
</inventoryItemLocationInformation>
<inventoryItemLocationInformation>
    <inventoryLocation>
        <additionalPartyIdentification
additionalPartyIdentificationTypeCode="88">BERGER</additionalPartyIdentification>
        </inventoryLocation>
    <transactionalTradelItem>
        <gtin>00000000000000</gtin>

```

```

                                <additionalTradeltemIdentification
additionalTradeltemIdentificationTypeCode="BUYER_ASSIGNED">444444444444</additionalTradeltemIdentific
ation>
                                <tradeltemQuantity
measurementUnitCode="PCE">14</tradeltemQuantity>
                                </transactionalTradeltem>
                                <inventoryStatusLineItem>
                                    <lineItemNumber>4</lineItemNumber>
                                    <inventoryStatusQuantitySpecification>

                                <inventoryStatusType>AVAILABLE_FOR_SALE</inventoryStatusType>
                                    <quantityOfUnits
measurementUnitCode="STK">14</quantityOfUnits>
                                    </inventoryStatusQuantitySpecification>
                                </inventoryStatusLineItem>
                                </inventoryItemLocationInformation>
                                <inventoryItemLocationInformation>
                                    <inventoryLocation>
                                        <additionalPartyIdentification
additionalPartyIdentificationTypeCode="88">BERGER</additionalPartyIdentification>
                                        </inventoryLocation>
                                        <transactionalTradeltem>
                                            <gtin>00000000000000</gtin>
                                            <additionalTradeltemIdentification
additionalTradeltemIdentificationTypeCode="BUYER_ASSIGNED">555555555555</additionalTradeltemIdentific
ation>
                                                <tradeltemQuantity measurementUnitCode="PCE">6</tradeltemQuantity>
                                                </transactionalTradeltem>
                                                <inventoryStatusLineItem>
                                                    <lineItemNumber>5</lineItemNumber>
                                                    <inventoryStatusQuantitySpecification>

                                                <inventoryStatusType>AVAILABLE_FOR_SALE</inventoryStatusType>
                                                    <quantityOfUnits
measurementUnitCode="STK">6</quantityOfUnits>
                                                    </inventoryStatusQuantitySpecification>
                                                </inventoryStatusLineItem>
                                                </inventoryItemLocationInformation>
                                </inventoryReport>
</ns0:inventoryReportMessage>

```