



Message Implementation Guideline

OrderResponse Axia

Model: OrderResponse Axia
Version: GS1 BMS 3.1
Variant: 1
Issue date: 2016-09-27
Author: Eva H Walldow

1 Structure.....	3
2 Guideline	4

Structure

Occurrence	Element/Attribute
	orderResponseMessage
1 .. 1	xsd:sequence
1 .. 1	sh:StandardBusinessDocumentHeader
1 .. 1	xsd:sequence
1 .. 1	HeaderVersion
1 .. unbounded	Sender
1 .. 1	xsd:sequence
1 .. 1	Identifier
	<i>Authority</i>
1 .. unbounded	Receiver
1 .. 1	xsd:sequence
1 .. 1	Identifier
	<i>Authority</i>
1 .. 1	DocumentIdentification
1 .. 1	xsd:sequence
1 .. 1	Standard
1 .. 1	TypeVersion
1 .. 1	Instanceldentification
1 .. 1	Type
1 .. 1	CreationDateAndTime
1 .. 10000	orderResponse
1 .. 1	xsd:sequence
1 .. 1	creationDateTime
1 .. 1	documentStatusCode
1 .. 1	xsd:sequence
1 .. 1	orderResponseIdentification
1 .. 1	xsd:sequence
1 .. 1	entityIdentification
1 .. 1	responseStatusCode
1 .. 1	buyer
1 .. 1	seller
1 .. 1	originalOrder
1 .. 1	xsd:sequence
1 .. 1	entityIdentification

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Guideline

Element/Attribute	Annotation
orderResponseMessage	Type order_response:OrderResponseMessageType
xsd:sequence	Occurrence 1 .. 1
sh:StandardBusinessDocumentHeader	Occurrence 1 .. 1 Type sh:StandardBusinessDocumentHeader
xsd:sequence	Occurrence 1 .. 1
HeaderVersion	Occurrence 1 .. 1 Type xsd:string Example 3.1
Sender	Occurrence 1 .. unbounded Type sh:Partner
xsd:sequence	Occurrence 1 .. 1
Identifier	Occurrence 1 .. 1 Type sh:PartnerIdentification Remark GLN for sender of the message Example 7300009035144
<i>Authority</i>	Type xsd:string Example 14
Receiver	Occurrence 1 .. unbounded Type sh:Partner
xsd:sequence	Occurrence 1 .. 1
Identifier	Occurrence 1 .. 1 Type sh:PartnerIdentification Remark Client Id Example 104599
<i>Authority</i>	Type xsd:string Example 14
DocumentIdentification	Occurrence 1 .. 1 Type sh:DocumentIdentification
xsd:sequence	Occurrence 1 .. 1
Standard	Occurrence 1 .. 1 Type xsd:string Example GS1 BMS
TypeVersion	Occurrence 1 .. 1 Type xsd:string Example 3.1
InstanceIdentifier	Occurrence 1 .. 1 Type xsd:string Example GS1
Type	Occurrence 1 .. 1 Type xsd:string Example OrderResponse
CreationDateAndTime	Occurrence 1 .. 1 Type xsd:dateTime Remark Message date/time Example 3014-09-25T09:50:00
orderResponse	Occurrence 1 .. 10000 Type order_response:OrderResponseType
xsd:sequence	Occurrence 1 .. 1
creationDateTime	Occurrence 1 .. 1 Type xsd:dateTime

Bold = Element, *Italic* = Attribute, Grey = Group



Element/Attribute	Annotation
documentStatusCode	Remark Document date/time Example 2014-09-25T09:50:00 Occurrence 1 .. 1 Type shared_common:DocumentStatusEnumerationType Example ORIGINAL
Applicable Codes	
ADDITIONAL	
xsd:sequence	Occurrence 1 .. 1
orderResponseIdentification	Occurrence 1 .. 1 Type shared_common:EntityIdentificationType
xsd:sequence	Occurrence 1 .. 1
entityIdentification	Occurrence 1 .. 1 Type restriction (xsd:string) Length 1 .. 80 Remark Customer Order number or other reference to the document Example 345678
responseStatusCode	Occurrence 1 .. 1 Type ecom_common:ResponseStatusCodeType Length 1 .. 80 Remark Status Code used in Axia Example O1
Applicable Codes	
O1 Mottatt EDI	
O3 Ordre allokert	
originalOrder	Occurrence 1 .. 1 Type shared_common:DocumentReferenceType
xsd:sequence	Occurrence 1 .. 1
entityIdentification	Occurrence 1 .. 1 Type restriction (xsd:string) Length 1 .. 80 Remark Original Customer Order number Example 125987

```

<?xml version="1.0" encoding="UTF-8" ?>
- <order_response:orderResponseMessage
  xmlns:order_response="urn:gs1:ecom:order_response:xsd:3"
  xmlns:sh="http://www.unece.org/cefact/namespaces/StandardBusinessDocum
entHeader">
- <sh:StandardBusinessDocumentHeader>
  <sh:HeaderVersion>3.1</sh:HeaderVersion>
- <sh:Sender>
  <sh:Identifier Authority="14">7300009035144</sh:Identifier>
  </sh:Sender>
- <sh:Receiver>
  <sh:Identifier Authority="14">104599</sh:Identifier>
  </sh:Receiver>
- <sh:DocumentIdentification>
  <sh:Standard>GS1 BMS</sh:Standard>
  <sh:TypeVersion>3.1</sh:TypeVersion>
  <sh:InstanceIdentifier>GS1</sh:InstanceIdentifier>
  <sh:Type>OrderResponse</sh:Type>
  <sh:CreationDateAndTime>2014-09-25T09:50:00</sh:CreationDateAndTime>
  </sh:DocumentIdentification>
  </sh:StandardBusinessDocumentHeader>
- <orderResponse>
  <creationDateTime>2014-09-25T09:50:00</creationDateTime>
  <documentStatusCode>ORIGINAL</documentStatusCode>
- <orderResponseIdentification>
  <entityIdentification>345678</entityIdentification>
  </orderResponseIdentification>
  <responseStatusCode>O1</responseStatusCode>
  <buyer />
  <seller />
- <originalOrder>
  <entityIdentification>125987</entityIdentification>
  </originalOrder>
  </orderResponse>
  </order_response:orderResponseMessage>

```